



**MODEL 4201** | Specification Sheet  
Commercial Series • Low Voltage • Path & Area

TYPE:  MODEL:

PROJECT:

**PRODUCT FEATURES**

Wattage	1.5 W
Voltage	9 – 15 VAC
Lumens	150 Lumens
Lamp Type	G4 LED
Housing	Aluminum
Dimensions	4" DIA x 19 1/8" H



**ORDERING INFORMATION**

EXAMPLE: PR-4201-B-2.5-W-G-T3

MOUNTING	MODEL	FINISH	LED
PR	4201		

MOUNTING	MODEL	FINISH	LED	ORDERING NOTES
PR ABS Ground Stake	4201	<b>B</b> Black	<b>150-W-G4</b> 1.5 Watts   Warm   G4 LED Lamp <b>NL</b> No Lamp	Fixtures shipped with specified mounting hardware.  Custom length stems available - Consult local distributor.
		<b>Z</b> Architectural Bronze		
		<b>DZ</b> Dark Bronze		
		<b>GT</b> Granite		
		<b>W</b> White		
		<b>BR</b> Architectural Brick		
		<b>LZ</b> Light Bronze		
		<b>SB</b> Special Bronze		
		<b>GG</b> Glossy Gray		
		<b>R</b> Rust		
		<b>HG</b> Hunter Green		
		<b>WB</b> Weathered Bronze		
		<b>WI</b> Weathered Iron		
		<b>GM</b> Graphite Metallic		
		<b>G</b> Verde		
<b>P</b> Pewter				
<b>M</b> Mocha				
<b>OF</b> Olde Finish				



**PROFESSIONAL  
OUTDOOR LIGHTING**

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



## SPECIFICATIONS

**HOUSING CONSTRUCTION:**

Die-cast A360 aluminum.

**STEM CONSTRUCTION:**

1" sq. aluminum tube.

**FINISH:**

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

**LENS:**

Clear, high-impact polycarbonate lens.

**MOUNTING:**

Bottom of stem fitted with 1/2" NPT Brass Connection.

**FASTENERS:**

All fasteners are stainless steel.

**WIRING:**

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

**CERTIFICATION:**

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

**LED:**

G4 LED Lamp.  
1.5 Watts.  
150 Lumens.

**ELECTRICAL:**

Input voltage range 9 - 15 VAC.  
Low voltage transformer required to operate (sold separately).

## DIMENSIONS

