



**ES Series | Specification Sheet**  
Commercial Series • Low Voltage • Transformer

TYPE:  MODEL:

PROJECT:

**PRODUCT FEATURES**

|                   |                                 |
|-------------------|---------------------------------|
| Wattage           | 150 W                           |
| Secondary Voltage | 12 and 15 VAC                   |
| Housing           | Stainless Steel                 |
| Dimensions        | 11 3/4" H x 6 1/8" W x 5 1/4" D |



**ORDERING INFORMATION**

EXAMPLE: ES-150DA

| SERIES | MODEL | OPTIONAL FINISH |
|--------|-------|-----------------|
| ES     |       |                 |

| SERIES   | MODEL  | OPTIONAL FINISH                   | ORDERING NOTES   |
|--|--|-----------------------------------|--|
| <b>ES</b> Energy Smart Low Voltage Transformer | <b>150</b> 150 Watts                           | Clear powder coat finish standard | <p>* See the following for accessory descriptions:</p> <p><b>T</b> Removable multi-setting mechanical 24-hour timer</p> <p><b>DA</b> Removable multi-setting digital astronomical timer</p> <p><b>RP</b> Remote wired photocell with electronic timer</p> <p>Accessories not required for operation of transformer</p> |
|  | <b>150T</b> 150 Watts   <b>T</b> timer *       | <b>B</b> Black                    |  |
|  | <b>150DA</b> 150 Watts   <b>DA</b> timer *     | <b>Z</b> Architectural Bronze     |  |
|  | <b>150RP</b> 150 Watts   <b>RP</b> photocell * | <b>DZ</b> Dark Bronze             |  |
|  |  | <b>GT</b> Granite                 |  |
|  |  | <b>W</b> White                    |  |
|  |  | <b>BR</b> Architectural Brick     |  |
|  |  | <b>LZ</b> Light Bronze            |  |
|  |  | <b>SB</b> Special Bronze          |  |
|  |  | <b>GG</b> Glossy Gray             |  |
|  |  | <b>R</b> Rust                     |  |
|  |  | <b>HG</b> Hunter Green            |  |
|  |  | <b>WB</b> Weathered Bronze        |  |
|  |  | <b>WI</b> Weathered Iron          |  |
|  |  | <b>GM</b> Graphite Metallic       |  |
|  |  | <b>G</b> Verde                    |  |
|  |  | <b>P</b> Pewter                   |  |
|  |  | <b>M</b> Mocha                    |  |
|  |  | <b>OF</b> Olde Finish             |  |



PROFESSIONAL  
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



## SPECIFICATIONS

### HOUSING CONSTRUCTION:

20-gauge 304 stainless steel.  
1/2"– 3/4" knockouts on each side of enclosure for conduit and accessory mounting as well as a removable, swing-down enclosure bottom with Adjustable Cable Raceway Feeder and 1/2"– 3/4" conduit knockout.

### NEMA ENCLOSURE RATING:

3R

### FINISH:

Clear powder coat finish standard. Also available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

### TERMINALS:

- Low voltage terminal strip for multiple cable connections
- 120-volt terminal strip for easy hard-wiring and an accessory terminal strip

### PRIMARY PROTECTION:

Auto thermal shut-off

### SECONDARY PROTECTION:

Resettable high performance magnetic circuit breaker.  
Fully grounded and isolated with encapsulated core and coil.

### WIRING:

6-foot, heavy-gauge, grounded, water-resistant power cord with integrally molded plug.

### CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

Pool & Spa Ready - Suitable for Use with Submersible Luminaires (power cord must be shortened to a 3-foot maximum length - see Installation Instructions).

### AVAILABLE POWER RATING:

150 Watts

### PRIMARY VOLTAGE:

120 Volts  
(Also available in 208V, 230V or 277V, 50 or 60 cycle - Special order only.)

### SECONDARY VOLTAGE:

12 and 15 Volts

## DIMENSIONS

