



**MODEL 2138** | Specification Sheet  
Commercial Series • Low Voltage • Bollard

TYPE:  MODEL:

PROJECT:

**PRODUCT FEATURES**



Wattage	4.5 W or 5.5 W
Voltage	9 – 15 VAC
Lumens	295 or 389 Lumens
Lamp Type	MR-16 LED
Housing	Copper or Stainless Steel
Dimensions	2 1/8" DIA x 16" H

**ORDERING INFORMATION**

EXAMPLE: **BR-2138-B-4.5-W-36**

**MOUNTING**                      **MODEL**                      **FINISH**                      **LED**  
BR                                      2138

MOUNTING	MODEL	FINISH	LED	ORDERING NOTES
BR ABS Ground Stake	2138	<b>CSN</b> Natural Copper  <b>SS</b> Stainless Steel	<b>4.5-W-15</b> 4.5 Watts   Warm   15° Narrow Spot	Fixtures shipped with specified mounting hardware.
			<b>4.5-W-25</b> 4.5 Watts   Warm   25° Spot	
			<b>4.5-W-36</b> 4.5 Watts   Warm   36° Flood	
			<b>4.5-W-60</b> 4.5 Watts   Warm   60° Wide Flood	
			<b>5.5-W-15</b> 5.5 Watts   Warm   15° Narrow Spot	
			<b>5.5-W-25</b> 5.5 Watts   Warm   25° Spot	
			<b>5.5-W-36</b> 5.5 Watts   Warm   36° Flood	
			<b>5.5-W-60</b> 5.5 Watts   Warm   60° Wide Flood	
			<b>NL</b> No Lamp	



**PROFESSIONAL  
OUTDOOR LIGHTING**

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



### SPECIFICATIONS

**CONSTRUCTION:**

Heavy-gauge, extruded, copper or stainless steel post fitted with machined solid brass cap.

**LENS:**

Clear, machined acrylic lens.

**MOUNTING:**

Aluminum mounting base with ABS ground stake included.

**FASTENERS:**

All fasteners are stainless steel.

**WIRING:**

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

**CERTIFICATION:**

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

**LED:**

MR-16 LED Lamp.  
295 or 389 Lumens.  
4.5 or 5.5 Watts.

**ELECTRICAL:**

Input voltage range 9 - 15 VAC.  
Low voltage transformer required to operate (sold separately).

### DIMENSIONS

