



**PROFESSIONAL
OUTDOOR LIGHTING**



Photometric Test Summary - Vista RK94 Series

File No.	Catalog Number	Description	Test Voltage	NEMA Type	Beam Angle (H/V)	Field Angle (H/V)	Total Lumens	Wattage	Efficacy	CRI	CCT
L021606604	RK94-B-NS-30-C-MV-CX-ND	Ingrade, NS Distribution	120VAC	2 H x 2 V	8.7 / 8.7	20.2 / 20.2	1737.56	25.4	68.41	84	3082
L061805937	RK94-B-NS-30-C-MV-CX-ND-LSF	Ingrade, NS + Linear Spread Filter Distribution	120VAC	4 H x 5 V	15.9 / 36.3	49.5 / 71.7	1863.3	25.47	73.15	83	2981
L021606605	RK94-B-MF-30-C-MV-CX-ND	Ingrade, MF Distribution	120VAC	3 H x 3 V	15.6 / 15.6	31.2 / 31.2	1766.3	25.69	68.76	85	3059
L061805940	RK94-B-MF-30-C-MV-CX-ND-LSF	Ingrade, MF + Linear Spread Filter Distribution	120VAC	4 H x 5 V	22.0 / 37.9	54.9 / 75.2	1930.74	25.44	75.89	83	2984
L021606606	RK94-B-WF-30-C-MV-CX-ND	Ingrade, WF Distribution	120VAC	4 H x 4 V	38.2 / 38.2	56.0 / 56.0	1625.1	25.69	63.27	84	3079
L021606616	RK94-B-NS-30-B-MV-CX-ND	Ingrade, NS Distribution	120VAC	2 H x 2 V	8.7 / 8.7	20.2 / 20.2	1407	20.57	68.41	84	3082
L061805938	RK94-B-NS-30-B-MV-CX-ND-LSF	Ingrade, NS + Linear Spread Filter Distribution	120VAC	4 H x 5 V	15.9 / 36.3	49.5 / 71.7	1509.54	20.63	73.15	83	2981
L021606617	RK94-B-MF-30-B-MV-CX-ND	Ingrade, MF Distribution	120VAC	3 H x 3 V	15.6 / 15.6	31.2 / 31.2	1431	20.81	68.76	85	3059
L061805941	RK94-B-MF-30-B-MV-CX-ND-LSF	Ingrade, MF + Linear Spread Filter Distribution	120VAC	4 H x 5 V	22.0 / 37.9	54.9 / 75.2	1563.8	20.61	75.89	83	2984
L021606618	RK94-B-WF-30-B-MV-CX-ND	Ingrade, WF Distribution	120VAC	4 H x 4 V	38.2 / 38.2	56.0 / 56.0	1317	20.81	63.27	84	3079
L061805946	RK94-B-VNS-30-A-MV-CX-ND	Ingrade, VNS Distribution	120VAC	2 H x 2 V	9.3 / 9.3	20.1 / 20.1	1141.04	25.52	44.71	83	3038
L061805947	RK94-B-VNS-30-A-MV-CX-ND-LSF	Ingrade, VNS + Linear Spread Filter Distribution	120VAC	3 H x 4 V	14.3 / 34.1	34.1 / 65.5	953.9	25.45	37.49	83	2996
L021606610	RK94-B-NS-30-A-MV-CX-ND	Ingrade, NS Distribution	120VAC	2 H x 2 V	8.7 / 8.7	20.2 / 20.2	981	14.34	68.41	84	3082
L061805939	RK94-B-NS-30-A-MV-CX-ND-LSF	Ingrade, NS + Linear Spread Filter Distribution	120VAC	4 H x 5 V	15.9 / 36.3	49.5 / 71.7	1043.58	14.26	73.15	83	2981
L021606611	RK94-B-MF-30-A-MV-CX-ND	Ingrade, MF Distribution	120VAC	3 H x 3 V	15.6 / 15.6	31.2 / 31.2	997	14.5	68.76	85	3059
L061805942	RK94-B-MF-30-A-MV-CX-ND-LSF	Ingrade, MF + Linear Spread Filter Distribution	120VAC	4 H x 5 V	22.0 / 37.9	54.9 / 75.2	1080.98	14.25	75.89	83	2984
L021606612	RK94-B-WF-30-A-MV-CX-ND	Ingrade, WF Distribution	120VAC	4 H x 4 V	38.2 / 38.2	56.0 / 56.0	917	14.5	63.27	84	3079
L061805943	RK94-B-MF-30-C-MV-CX-ND-LSF-T015	Ingrade, Wall Wash Distribution	120VAC	5 H x 5 V	37.8 / 23.1	74.7 / 74.2	1810.66	25.38	71.34	83	3016
L061805944	RK94-B-MF-30-B-MV-CX-ND-LSF-T015	Ingrade, Wall Wash Distribution	120VAC	5 H x 5 V	37.8 / 23.1	74.7 / 74.2	1466.58	20.56	71.34	83	3016
L061805945	RK94-B-MF-30-A-MV-CX-ND-LSF-T015	Ingrade, Wall Wash Distribution	120VAC	5 H x 5 V	37.8 / 23.1	74.7 / 74.2	1014.22	14.21	71.34	83	3016

LED LM-79 Flood Report includes Report Summary, Axial Candela Calculations, Axial Candela Display & Isocandela Curves