



**PROFESSIONAL  
OUTDOOR LIGHTING**



## Photometric Test Summary: Vista 1052 Series

File No.	Catalog Number	Description	Beam Angle (H°xV°)	NEMA TYPE	Max Candela	Max Candela Angle	Total Lumens	Wattage	Efficacy	CCT
L092110503	1052-X-NS-X-B-MV-ND	LED Linear Floodlight, NS Distribution	87° x 22°	7H x 4V	3087	-1H, 0V	2553	35.5	72	4131
L092110504	1052-X-MF-X-B-MV-ND	LED Linear Floodlight, MF Distribution	94° x 53°	7H x 5V	2728	-1H, 7V	3690	35.8	103	3213
L092110505	1052-X-WF-B-MV-ND	LED Linear Floodlight, WF Distribution	76° x 84°	7H x 7V	1533	0H, -17V	3099	35.6	87	3215
L092110502	1052-X-WG-B-MV-ND	LED Linear Floodlight, WG Distribution	87° x 20°	7H x 4V	5253	-1H, -5V	3635	35.5	103	3208
L092110501	1052-X-WW-B-MV-ND	LED Linear Floodlight, WW Distribution	76° x 43°	6H x 6V	2150	0H, -22.5V	3132	35.6	88	3218
L072310304	1052-X-AS-B-MV-ND	LED Linear Floodlight, AS Distribution	104° x 76°	7H x 5V	2159	1H, 37.5V	3914	36.6	107	3100
L092112403	1052-X-NS-X-A-MV-ND	LED Linear Floodlight, NS Distribution	86° x 21°	6H x 4V	2237	-1H, 0V	1821	26.0	70	3254
L092112404	1052-X-MF-X-A-MV-ND	LED Linear Floodlight, MF Distribution	94° x 53°	7H x 5V	2012	-3H, -7V	2696	26.0	104	3238
L092112405	1052-X-WF-A-MV-ND	LED Linear Floodlight, WF Distribution	77° x 84°	7H x 7V	1137	-1H, 17V	2307	26.0	89	3222
L092112402	1052-X-WG-A-MV-ND	LED Linear Floodlight, WG Distribution	98° x 20°	7H x 4V	3904	0H, 5V	2631	26.0	101	3227
L092112401	1052-X-WW-A-MV-ND	LED Linear Floodlight, WW Distribution	75° x 42°	6H x 6V	1587	0H, 22.5V	2289	26.1	88	3189
L072310303	1052-X-AS-A-MV-ND	LED Linear Floodlight, AS Distribution	102° x 76°	7H x 5V	1726	0H, 42.5V	3044	27.7	110	3059

\*LED Flood Report includes LM-79 Report, Report Summary, Axial Display, Isocandela.

\*\*Photometrics derived from 1142-X testing.