



**MT Series | Specification Sheet**  
Commercial Series · Low Voltage · Transformer

TYPE:  MODEL:

PROJECT:

**PRODUCT FEATURES**

Wattage	300 – 1200 W
Secondary Voltage	11 – 15 VAC
Housing	Stainless Steel
Dimensions	17" H x 9" W x 5 1/2" D



**ORDERING INFORMATION**

EXAMPLE: **MT-600DT**

**SERIES**                      **MODEL**                      **OPTIONAL FINISH**

MT

SERIES	MODEL	OPTIONAL FINISH	ORDERING NOTES
<b>MT</b> Multi-Tap Transformer	<b>300</b> 300 Watts	Clear powder coat finish standard	<p>* See the following for accessory descriptions:</p> <p><b>T</b> Removable multi-setting mechanical 24-hour timer</p> <p><b>DT</b> Removable multi-setting digital 7-day timer</p> <p><b>DA</b> Removable multi-setting digital astronomical timer</p> <p><b>RP</b> Remote wired photocell with electronic timer</p> <p>Accessories not required for operation of transformer</p>
	<b>300T</b> 300 Watts   <b>T</b> timer *	<b>B</b> Black	
	<b>300DT</b> 300 Watts   <b>DT</b> timer *	<b>Z</b> Architectural Bronze	
	<b>300DA</b> 300 Watts   <b>DA</b> timer *	<b>DZ</b> Dark Bronze	
	<b>300RP</b> 300 Watts   <b>RP</b> photocell *	<b>GT</b> Granite	
	<b>600</b> 600 Watts (300 W x 2)	<b>W</b> White	
	<b>600T</b> 600 Watts (300 W x 2)   <b>T</b> timer *	<b>BR</b> Architectural Brick	
	<b>600DT</b> 600 Watts (300 W x 2)   <b>DT</b> timer *	<b>LZ</b> Light Bronze	
	<b>600DA</b> 600 Watts (300 W x 2)   <b>DA</b> timer *	<b>SB</b> Special Bronze	
	<b>600RP</b> 600 Watts (300 W x 2)   <b>RP</b> photocell *	<b>GG</b> Glossy Gray	
	<b>900</b> 900 Watts (300 W x 3)	<b>R</b> Rust	
	<b>900T</b> 900 Watts (300 W x 3)   <b>T</b> timer *	<b>HG</b> Hunter Green	
	<b>900DT</b> 900 Watts (300 W x 3)   <b>DT</b> timer *	<b>WB</b> Weathered Bronze	
	<b>900RP</b> 900 Watts (300 W x 3)   <b>RP</b> photocell *	<b>WI</b> Weathered Iron	
	<b>1200</b> 1200 Watts (300 W x 4)	<b>GM</b> Graphite Metallic	
	<b>1200T</b> 1200 Watts (300 W x 4)   <b>T</b> timer *	<b>G</b> Verde	
<b>1200DT</b> 1200 Watts (300 W x 4)   <b>DT</b> timer *	<b>P</b> Pewter		
<b>1200RP</b> 1200 Watts (300 W x 4)   <b>RP</b> photocell *	<b>M</b> Mocha		
	<b>OF</b> Olde Finish		



**PROFESSIONAL OUTDOOR LIGHTING**

www.VistaPro.com · email@vistapro.com · Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue · Simi Valley, CA 93063 · (805) 527-0987 · (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



**SPECIFICATIONS**

**HOUSING CONSTRUCTION:**

20-gauge 304 stainless steel.  
1/2"– 3/4" knockouts on each side of enclosure for conduit and accessory mounting as well as a removable, swing-down enclosure bottom with Adjustable Cable Raceway Feeder and multiple 1/2"– 3/4" and 2" knockouts.

**NEMA ENCLOSURE RATING:**

3R

**FINISH:**

Clear powder coat finish standard. Also available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

**TERMINALS:**

- Low voltage terminal strip for multiple cable connections
- 120-volt terminal strip for easy hard-wiring and an accessory terminal strip

**PRIMARY PROTECTION:**

Auto thermal shut-off

**SECONDARY PROTECTION:**

Resettable high performance magnetic circuit breaker.  
Fully grounded and isolated with encapsulated core and coil.

**WIRING:**

6-foot, heavy-gauge, grounded, water-resistant power cord with integrally molded plug.

**CERTIFICATION:**

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838). Pool & Spa Ready - Suitable for use with submersible luminaires or submersible pumps (power cord must be shortened to a 3-foot maximum length - see Installation Instructions).

**AVAILABLE POWER RATING:**

300, 600, 900 or 1200 Watts

**PRIMARY VOLTAGE:**

120 Volts  
(Also available in 208V, 230V or 277V, 50 or 60 cycle - Special order only.)

**SECONDARY VOLTAGE:**

11, 12, 13, 14 and 15 Volts

**DIMENSIONS**

