



**MODEL 4217** | Specification Sheet  
Commercial Series • Low Voltage • Underwater

TYPE:  MODEL:   
PROJECT:

**PRODUCT FEATURES**



Wattage	2.5 – 5 W
Voltage	9 – 15 VAC
Housing	Injection-Molded Polymer
Dimensions	4 3/4" DIA x 3" H



**ORDERING INFORMATION**

EXAMPLE: UW-4217-B-W-LB5ND-DBL

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
UW	4217	B		

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
UW Underwater	4217	B Black	<b>W-LB2ND</b> 2.5 Watts   Warm   Integrated LED	<b>DBL</b> Dark Blue Lens <b>GL</b> Dark Green Lens <b>RL</b> Red Lens <b>YL</b> Amber Lens
			<b>N-LB2ND</b> 2.5 Watts   Neutral   Integrated LED	
			<b>C-LB2ND</b> 2.5 Watts   Cool   Integrated LED	
			<b>W-LB5ND</b> 5 Watts   Warm   Integrated LED	
			<b>N-LB5ND</b> 5 Watts   Neutral   Integrated LED	
			<b>C-LB5ND</b> 5 Watts   Cool   Integrated LED	
				<b>ORDERING NOTES</b>
				4217 <b>NOT</b> for use in swimming pools or spas.



**PROFESSIONAL**  
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



## SPECIFICATIONS

**HOUSING CONSTRUCTION:**

Injection-molded polymer.

**LENS CONSTRUCTION:**

Injection-molded polycarbonate.

**LENS:**

Clear prismatic spread lens.  
Optical effect lenses are available.

**REFLECTOR:**

Removable mirror-finish reflector to block up light and provide wider horizontal spread.

**FASTENERS:**

All fasteners are stainless steel.

**WIRING:**

Pre-wired with a fifteen-foot pigtail of 18-3 submersible cable.  
Connectors for a required above-water connection are also included.

**CAUTION:**

Follow installation instructions as well as local electrical codes when installing.  
**NOT** for use in swimming pools or spas.

**LED:**

Integrated LED Module.  
2.5 – 5 Watts.

**ELECTRICAL:**

Input voltage range 9 - 15 VAC.  
Low voltage transformer required to operate (sold separately).

## DIMENSIONS

