



**MODEL 6570** | Specification Sheet  
Commercial Series • Low Voltage • Path & Area

TYPE:  MODEL:

PROJECT:

**PRODUCT FEATURES**



Wattage	1 W
Voltage	9 – 15 VAC
CCT	3000K (WARM)   5000K (COOL)
Housing	Aluminum
Dimensions	1½" W x 7" D x 20" H



EXAMPLE: PR-6570-B-W-LB2ND

**ORDERING INFORMATION**

MOUNTING	MODEL	FINISH	LED
PR	6570		

MOUNTING	MODEL	FINISH	LED	ORDERING NOTES
PR ABS Ground Stake	6570	<b>B</b> Black	<b>W-LB2ND</b> 1 Watt   Warm   Integrated LED <b>C-LB2ND</b> 1 Watt   Cool   Integrated LED	Fixtures shipped with specified mounting hardware.  Custom length stems available - Consult local distributor.
		<b>Z</b> Architectural Bronze		
		<b>DZ</b> Dark Bronze		
		<b>GT</b> Granite		
		<b>W</b> White		
		<b>BR</b> Architectural Brick		
		<b>LZ</b> Light Bronze		
		<b>SB</b> Special Bronze		
		<b>GG</b> Glossy Gray		
		<b>R</b> Rust		
		<b>HG</b> Hunter Green		
		<b>WB</b> Weathered Bronze		
		<b>WI</b> Weathered Iron		
		<b>GM</b> Graphite Metallic		
		<b>G</b> Verde		
<b>P</b> Pewter				
<b>M</b> Mocha				
<b>OF</b> Olde Finish				





**SPECIFICATIONS**

**HOUSING CONSTRUCTION:**

Die-cast A360 aluminum.

**STEM CONSTRUCTION:**

1" x 1.5" aluminum tube.

**FINISH:**

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

**LENS:**

Textured, high-impact polycarbonate lens.

**MOUNTING:**

Bottom of stem fitted with 1/2" NPT Brass Connection.

**FASTENERS:**

All fasteners are stainless steel.

**WIRING:**

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

**CERTIFICATIONS | STANDARDS | COMPLIANCE:**

- UL Certified for wet locations (USA & Canada) | (UL 1838)
- Buy American Act (BAA)
- Build America, Buy America Act (BABA)

**LED:**

Integrated LED Module.

1 Watt.

**COLOR TEMPERATURE:**

3000K or 5000K CCT White.

**ELECTRICAL:**

Input voltage range 9 - 15 VAC.

Low voltage transformer required to operate (sold separately).

**DIMENSIONS**

