



**MODEL 2111** | Specification Sheet  
 Commercial Series • Low Voltage • Up / Accent / Downlight

TYPE:  MODEL:   
 PROJECT:

**PRODUCT FEATURES**



Wattage	2.5 W
Voltage	9 – 15 VAC
Lumens	200 Lumens
Lamp Type	MR-11 LED
Housing	Copper
Dimensions	1 5/8" DIA x 6 3/8" D



**ORDERING INFORMATION**

EXAMPLE: GR-2111-CSN-2.5-W-36-FR

MOUNTING	MODEL	FINISH	LED	ACCESSORIES
	2111	CSN		

MOUNTING	MODEL	FINISH	LED	ACCESSORIES
<b>GR</b> ABS Ground Stake <b>WB</b> Brass Wall-Mount Canopy	2111	CSN Natural Copper	<b>2.5-W-15</b> 2.5 Watts   Warm   15° Narrow Spot <b>2.5-W-25</b> 2.5 Watts   Warm   25° Spot <b>2.5-W-36</b> 2.5 Watts   Warm   36° Flood <b>2.5-W-60</b> 2.5 Watts   Warm   60° Wide Flood <b>NL</b> No Lamp	<b>FR</b> Frosted Lens <b>BL</b> Flat Cool Blue Lens <b>SL</b> Flat Spread Lens <b>DBL</b> Flat Dark Blue Lens <b>GL</b> Flat Dark Green Lens <b>RL</b> Flat Red Lens <b>YL</b> Flat Amber Lens <b>HL</b> Honeycomb louver <b>5</b> 5' Wire Lead
				<b>ORDERING NOTES</b> Fixtures shipped with specified mounting hardware.  If fixture is to be used in conjunction with Extended Arm Mount ( <b>EAM</b> ): Must specify with extended wire length



PROFESSIONAL  
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
 1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



### SPECIFICATIONS

**HOUSING CONSTRUCTION:**

Heavy-gauge, extruded copper with machined brass base.

**LENS:**

Clear, tempered glass lens.  
Optical effect lenses are available.

**MOUNTING:**

Solid Brass knuckle with 1/2" NPS thread.

**FASTENERS/INSERTS:**

Fasteners are stainless steel and brass.

**WIRING:**

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

**CERTIFICATION:**

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

**LED:**

MR-11 LED Lamp.  
200 Lumens.  
2.5 Watts.

**ELECTRICAL:**

Input voltage range 9 - 15 VAC.  
Low voltage transformer required to operate (sold separately).

**LIGHT DISTRIBUTION:**

Very Narrow Spot **15** (15°)  
Narrow Spot **25** (25°)  
Medium Flood **36** (36°)  
Wide Flood **60** (60°)

### DIMENSIONS

