



**PROFESSIONAL  
OUTDOOR LIGHTING**



## Photometric Test Summary - Vista 1059 Series

File No.	Catalog Number	Description	Test Voltage	NEMA Type	Beam Angle (H/V)	Field Angle (H/V)	Total Lumens	Wattage	Efficacy	CRI	CCT
L081407402	1059-X-VNS-30-B-MV-ND	Floodlight, VNS Distribution	120VAC	2 H x 2 V	11.6 / 11.6	22.1 / 22.1	2459.9	59.69	41.21	82	3091
L061805914	1059-X-VNS-30-B-MV-ND-LSF	Floodlight, VNS + Linear Spread Filter Distribution	120VAC	3 H x 4 V	13.8 / 34.6	29.8 / 65.2	1720.32	59.07	29.12	82	2993
L081407401	1059-X-VNS-30-C-MV-ND	Floodlight, VNS Distribution	120VAC	2 H x 2 V	11.3 / 11.3	21.9 / 21.9	2792.88	74.08	37.7	82	3130
L061805913	1059-X-VNS-30-C-MV-ND-LSF	Floodlight, VNS + Linear Spread Filter Distribution	120VAC	3 H x 4 V	13.8 / 34.6	29.8 / 65.2	2150.3	73.84	29.12	82	2993
L081407403	1059-X-NS-30-D-MV-ND	Floodlight, NS Distribution	120VAC	2 H x 2 V	11.7 / 11.7	22.6 / 22.6	3558.74	48.1	73.99	83	3129
L061805912	1059-X-NS-30-D-MV-ND-LSF	Floodlight, NS + Linear Spread Filter Distribution	120VAC	3 H x 4 V	14.8 / 35.6	45.0 / 69.3	2420.52	44.05	54.95	82	3152
L081407404	1059-X-MF-30-D-MV-ND	Floodlight, MF Distribution	120VAC	5 H x 5 V	60.5 / 56.6	74.8 / 73.4	3407.2	48.2	70.68	82	3106
L061805918	1059-X-MF-30-D-MV-ND-LSF	Floodlight, MF + Linear Spread Filter Distribution	120VAC	5 H x 5 V	48.0 / 48.1	79.0 / 91.5	2163.26	43.3	49.95	82	2978
L081407405	1059-X-WF-30-D-MV-ND	Floodlight, WF Distribution	120VAC	6 H x 6 V	83.2 / 54.2	123.6 / 111.7	3198.96	47.88	66.82	83	3168
L081407406	1059-X-NS-30-E-MV-ND	Floodlight, NS Distribution	120VAC	2 H x 2 V	11.6 / 11.6	22.6 / 22.6	3874.24	49.48	78.3	82	3135
L061805911	1059-X-NS-30-E-MV-ND-LSF	Floodlight, NS + Linear Spread Filter Distribution	120VAC	3 H x 4 V	14.8 / 35.6	45.0 / 69.3	2743.04	49.93	54.94	82	3152
L081407407	1059-X-MF-30-E-MV-ND	Floodlight, MF Distribution	120VAC	5 H x 5 V	60.5 / 56.6	74.7 / 73.4	3744.26	49.5	75.65	82	3096
L061805917	1059-X-MF-30-E-MV-ND-LSF	Floodlight, MF + Linear Spread Filter Distribution	120VAC	5 H x 5 V	48.0 / 48.1	79.0 / 91.5	2451.74	49.08	49.95	82	2978
L081407408	1059-X-WF-30-E-MV-ND	Floodlight, WF Distribution	120VAC	6 H x 6 V	83.2 / 54.3	123.5 / 111.7	3475.92	49.26	70.56	83	3162
L081407409	1059-X-NS-30-F-MV-ND	Floodlight, NS Distribution	120VAC	2 H x 2 V	11.4 / 11.4	22.5 / 22.5	4280.52	59.49	71.95	82	3152
L061805910	1059-X-NS-30-F-MV-ND-LSF	Floodlight, NS + Linear Spread Filter Distribution	120VAC	3 H x 4 V	14.8 / 35.6	45.0 / 69.3	3227.16	58.74	54.94	82	2996
L081407410	1059-X-MF-30-F-MV-ND	Floodlight, MF Distribution	120VAC	5 H x 5 V	60.3 / 56.4	74.8 / 73.5	4150.94	59.75	69.47	82	3132
L061805916	1059-X-MF-30-F-MV-ND-LSF	Floodlight, MF + Linear Spread Filter Distribution	120VAC	5 H x 5 V	48.0 / 48.1	79.0 / 91.5	2883.9	57.74	49.95	82	2978
L081407411	1059-X-WF-30-F-MV-ND	Floodlight, WF Distribution	120VAC	6 H x 6 V	82.1 / 62.9	122.6 / 115.3	3932.52	59.38	66.23	82	3186
L081407412	1059-X-NS-30-G-MV-ND	Floodlight, NS Distribution	120VAC	2 H x 2 V	11.6 / 11.6	22.5 / 22.5	5180.75	74.14	69.88	82	3148
L061805909	1059-X-NS-30-G-MV-ND-LSF	Floodlight, NS + Linear Spread Filter Distribution	120VAC	3 H x 4 V	14.8 / 35.6	45.0 / 69.3	4034	73.42	54.95	82	2996
L081407413	1059-X-MF-30-G-MV-ND	Floodlight, MF Distribution	120VAC	5 H x 5 V	60.5 / 56.6	74.7 / 73.4	4971.86	74.13	67.07	82	3130
L061805915	1059-X-MF-30-G-MV-ND-LSF	Floodlight, MF + Linear Spread Filter Distribution	120VAC	5 H x 5 V	48.0 / 48.1	79.0 / 91.5	3605.04	72.17	49.95	82	2978
L081407414	1059-X-WF-30-G-MV-ND	Floodlight, WF Distribution	120VAC	6 H x 6 V	82.8 / 62.9	123.1 / 115.2	4565.98	73.82	61.85	82	3202
L032113501	1059-X-VNS-30-H-MV-ND	LED Floodlight, VNS Distribution	120VAC	2 H x 2 V	11.3 / 12.8	23.7 / 24.5	5887	95.5	61.6	82.7	3089
L032113502	1059-X-NS-30-H-MV-ND	LED Floodlight, NS Distribution	120VAC	2 H x 2 V	13.9 / 13.9	27.3 / 27.4	9333	95.6	97.65	82.6	3095
L032113503	1059-X-MF-30-H-MV-ND	LED Floodlight, MF Distribution	120VAC	5 H x 5 V	57.3 / 60.5	72.8 / 74.8	9550	95.6	99.89	82.6	3071
L042111101	1059-X-WF-30-H-MV-ND	LED Floodlight, WF Distribution	120VAC	7 H x 7 V	82.5 / 82.5	130.5 / 130.5	9340	95.2	98.08	82.5	3125
L032111501	1059-X-VNS-30-I-MV-ND	LED Floodlight, VNS Distribution	120VAC	2 H x 2 V	12.1 / 13.4	24.5 / 25.1	6416	112.4	57.09	82.6	3110
L022113001	1059-X-NS-30-I-MV-ND	LED Floodlight, NS Distribution	120VAC	2 H x 2 V	13.5 / 14.7	28.3 / 28.9	10360	112.5	92.09	82.6	3124
L022112401	1059-X-MF-30-I-MV-ND	LED Floodlight, MF Distribution	120VAC	5 H x 5 V	57.2 / 60.3	73.1 / 75	10708	112.7	95.01	82.5	3098
L042112405	1059-X-WF-30-I-MV-ND	LED Floodlight, WF Distribution	120VAC	7 H x 7 V	82.1/82.1	130.3/130.3	10301	112.26	91.76	82.2	3171

LED LM-79 Flood Report includes Report Summary, Axial Candela Calculations, Axial Candela Display & Isocandela Curves

LED LM-79 Flood Report includes Report Summary, Axial Candela Calculations, Axial Candela Display & Isocandela Curves