



MODEL 4263 | Specification Sheet
Commercial Series • Low Voltage • Step Light

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	10 W
Voltage	9 – 15 VAC
Faceplate	Aluminum, Brass, Copper or Stainless Steel
Dimensions	24" L x 7/8" H x 3 1/4" D

ORDERING INFORMATION

EXAMPLE: *SL-4263-BSN-W-LB2ND*

CATEGORY	MODEL	FINISH	LED
SL	4263		

CATEGORY	MODEL	FINISH	LED
SL Step Light	4263	B Black	W-LB2ND 2.5 Watts (x4) Warm Integrated LED C-LB2ND 2.5 Watts (x4) Cool Integrated LED
		Z Architectural Bronze	
		DZ Dark Bronze	
		GT Granite	
		W White	
		BR Architectural Brick	
		LZ Light Bronze	
		SB Special Bronze	
		GG Glossy Gray	
		BSN Natural Brass	
BZO Olde Brass			
		R Rust HG Hunter Green WB Weathered Bronze WI Weathered Iron GM Graphite Metallic G Verde P Pewter M Mocha OF Olde Finish CSN Natural Copper SS Stainless Steel	



PROFESSIONAL
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

FACEPLATE CONSTRUCTION:

Aluminum, Brass, Copper or Stainless Steel.

HOUSING CONSTRUCTION:

Die-cast A360 aluminum.

FLANGE CONSTRUCTION:

Aluminum, Brass, Copper or Stainless Steel.

FINISH:

Aluminum Housing available with Powder coat finish in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

LENS:

Textured, high-impact polycarbonate lens.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a ten-foot pigtail of 18-2 SPT1 cable and underground connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

Integrated LED Module. 10 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.

Low voltage transformer required to operate (sold separately).

DIMENSIONS

