



**MODEL 5014i** | Specification Sheet  
 Commercial Series • Low Voltage • Up / Accent / Downlight

TYPE:  MODEL:   
 PROJECT:

**PRODUCT FEATURES**



Wattage	2 – 4 W
Voltage	9 – 15 VAC
Lumens	180 – 400 Delivered Lumens
Distribution	25° (SP), 36° (MF), 60° (WF)
CCT	3000K, 4000K, 5000K
CRI	80 CRI min.
Housing	Die-cast Aluminum
Dimensions	2 1/8" DIA x 5 5/8" D



**ORDERING INFORMATION**

EXAMPLE: GR-5014i-B-2.5-W-SP-IK-HL

MOUNTING	MODEL	FINISH	WATTAGE	COLOR TEMP	DISTRIBUTION	KNUCKLE	ACCESSORIES
	5014i					IK	

MOUNTING	MODEL	FINISH				WATTAGE
<b>GR</b> ABS ground stake <b>WR</b> Wall-mount canopy <b>TR</b> Tree-mount junction box	<b>5014i</b>	<b>B</b> Black <b>Z</b> Architectural Bronze <b>DZ</b> Dark Bronze <b>GT</b> Granite <b>W</b> White	<b>BR</b> Architectural Brick <b>LZ</b> Light Bronze <b>SB</b> Special Bronze <b>GG</b> Glossy Gray <b>R</b> Rust <b>HG</b> Hunter Green <b>WB</b> Weathered Bronze <b>WI</b> Weathered Iron <b>GM</b> Graphite Metallic	<b>G</b> Verde <b>P</b> Pewter <b>M</b> Mocha <b>OF</b> Olde Finish	<b>1.5</b> 2 Watts <b>2.5</b> 3 Watts <b>3.5</b> 4 Watts	
COLOR TEMPERATURE	DISTRIBUTION	KNUCKLE	ACCESSORIES	ORDERING NOTES		
<b>W</b> 3000K <b>N</b> 4000K <b>C</b> 5000K	<b>SP</b> 25° Spot <b>MF</b> 36° Flood <b>WF</b> 60° Wide Flood	<b>IK</b> Infinity Knuckle	<b>FR</b> Frosted Lens <b>5</b> 5' Wire Lead	Fixtures shipped with specified mounting hardware.  If fixture is to be used in conjunction with Extended Arm Mount ( <b>EAM</b> ): Must specify with extended wire length		



PROFESSIONAL  
 OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
 1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



## SPECIFICATIONS

### HOUSING CONSTRUCTION:

Die-cast A360 aluminum.

### FINISH:

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish. Custom Powder coat finishes available on request.

### LENS:

Clear, tempered glass lens.  
Optical effect lenses are available.

### FASTENERS:

All fasteners are stainless steel.

### WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

### MOUNTING:

Infinity Knuckle – Die-cast, copper-free aluminum, stainless steel stem with 1/2" NPT thread. A fully sealed spherical grommet allows for precise aiming and retention.

### CERTIFICATIONS | STANDARDS | COMPLIANCE:

- UL Certified for wet locations (USA & Canada) | (UL 1838)
- Buy American Act (BAA)
- Build America, Buy America Act (BABA)

### LED:

Performance LED.  
180 – 400 Lumens delivered.  
2 – 4 Watts.

### COLOR TEMPERATURE:

3000K, 4000K or 5000K CCT White.

### COLOR RENDERING:

80 CRI minimum

### ELECTRICAL:

Input voltage range 9 - 15 VAC.  
Low voltage transformer required to operate (sold separately).

### LIGHT DISTRIBUTION:

Spot **SP** (25°)  
Medium Flood **MF** (36°)  
Wide Flood **WF** (60°)

## DIMENSIONS

