



**MODEL 4263** | Specification Sheet  
Commercial Series • Low Voltage • Step Light

TYPE:  MODEL:

PROJECT:

**PRODUCT FEATURES**



Wattage	3 W
Voltage	9 – 15 VAC
CCT	3000K (WARM)   5000K (COOL)
Faceplate	Aluminum, Brass, Copper or Stainless Steel
Dimensions	24" L x 7/8" H x 3 1/4" D

**ORDERING INFORMATION**

EXAMPLE: **SL-4263-BSN-W-LB2ND**

CATEGORY	MODEL	FINISH	LED
SL	4263		

CATEGORY	MODEL	FINISH	LED
SL Step Light	4263	<b>B</b> Black <b>R</b> Rust <b>Z</b> Architectural Bronze <b>HG</b> Hunter Green <b>DZ</b> Dark Bronze <b>WB</b> Weathered Bronze <b>GT</b> Granite <b>WI</b> Weathered Iron <b>W</b> White <b>GM</b> Graphite Metallic <b>BR</b> Architectural Brick <b>G</b> Verde <b>LZ</b> Light Bronze <b>P</b> Pewter <b>SB</b> Special Bronze <b>M</b> Mocha <b>GG</b> Glossy Gray <b>OF</b> Olde Finish	<b>W-LB2ND</b> 3 Watts total   Warm   Integrated LED <b>C-LB2ND</b> 3 Watts total   Cool   Integrated LED
		<b>BSN</b> Natural Brass <b>CSN</b> Natural Copper <b>BSO</b> Olde Brass <b>SS</b> Stainless Steel	



PROFESSIONAL  
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



## SPECIFICATIONS

### FACEPLATE CONSTRUCTION:

Aluminum, Brass, Copper or Stainless Steel.

### HOUSING CONSTRUCTION:

Die-cast A360 aluminum.

### FLANGE CONSTRUCTION:

Aluminum, Brass, Copper or Stainless Steel.

### FINISH:

Aluminum Housing available with Powder coat finish in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

### LENS:

Textured, high-impact polycarbonate lens.

### FASTENERS:

All fasteners are stainless steel.

### WIRING:

Prewired with a ten-foot pigtail of 18-2 SPT1 cable and underground connectors.

### CERTIFICATIONS | STANDARDS | COMPLIANCE:

- UL Certified for wet locations (USA & Canada) | (UL 1838)
- Buy American Act (BAA)
- Build America, Buy America Act (BABA)

### LED:

Integrated LED Module.  
3 Watts total.

### COLOR TEMPERATURE:

3000K or 5000K CCT White.

### ELECTRICAL:

Input voltage range 9 - 15 VAC.  
Low voltage transformer required to operate (sold separately).

## DIMENSIONS

