



MODEL 5105 | Specification Sheet
 Commercial Series • Low Voltage • Up / Accent / Downlight

TYPE: MODEL:
 PROJECT:

PRODUCT FEATURES



| | |
|------------|----------------------|
| Wattage | 2 – 4 W |
| Voltage | 9 – 15 VAC |
| CCT | 3000K, 4000K, 5000K |
| Housing | Die-cast Aluminum |
| Dimensions | 3¼" W x 3⅞" H x 2" D |



ORDERING INFORMATION

EXAMPLE: GR-5105-B-2-W-FR

| MOUNTING | MODEL | FINISH | WATTAGE | COLOR TEMP | ACCESSORIES |
|----------|-------|--------|---------|------------|-------------|
| | 5105 | | | | |

| MOUNTING | MODEL | FINISH | | |
|--|--|---|--|--|
| GR ABS ground stake WR Wall-mount canopy TR Tree-mount junction box | 5105 | B Black Z Architectural Bronze DZ Dark Bronze GT Granite W White | BR Architectural Brick LZ Light Bronze SB Special Bronze GG Glossy Gray R Rust HG Hunter Green WB Weathered Bronze WI Weathered Iron GM Graphite Metallic | G Verde P Pewter M Mocha OF Olde Finish |
| WATTAGE | COLOR TEMPERATURE | ACCESSORIES | ORDERING NOTES | |
| 2 2 Watts 3 3 Watts 4 4 Watts | W 3000K N 4000K C 5000K | FR Frosted Lens 5 5' Wire Lead | Fixtures shipped with specified mounting hardware. If fixture is to be used in conjunction with Extended Arm Mount (EAM): Must specify with extended wire length | |



PROFESSIONAL
 OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
 1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Die-cast A360 aluminum. Optic and driver compartment environmentally sealed.

FINISH:

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish. Custom Powder coat finishes available on request.

LENS:

Clear, tempered glass lens.
Optical effect lenses are available.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

MOUNTING:

Injection-molded composite knuckle with 1/2" NPS thread.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

Performance LED. 2 – 4 Watts.

COLOR TEMPERATURE:

3000K, 4000K or 5000K CCT White.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

DIMENSIONS

