

# **PRODUCT FEATURES**

Wattage	1 – 5 W
Voltage	9 – 15 VAC
Housing	Copper
Dimensions	9" W ×25" H





EXAMPLE: PR-2155-CSN-W-LB5ND

# **ORDERING INFORMATION**

MOUNTINGMODELFINISHLEDPR2155CSN

MOUNTING	MODEL	FINISH	LED
PR ABS Ground Stake	2155	CSN Natural Copper	W-LB2ND 2.5 Watts   Warm   Integrated LED
			N-LB2ND 2.5 Watts   Neutral   Integrated LED
			C-LB2ND 2.5 Watts   Cool   Integrated LED
			W-LB5ND 5 Watts   Warm   Integrated LED
			N-LB5ND 5 Watts   Neutral   Integrated LED
			C-LB5ND 5 Watts   Cool   Integrated LED
			<b>150-W-G4</b> 1.5 Watts   Warm   G4 LED Lamp
			<b>NL</b> No Lamp



## **SPECIFICATIONS**

# HOUSING CONSTRUCTION:

Die-cast A360 aluminum with stamped copper petals.

### STEM CONSTRUCTION:

 $\frac{1}{4}$ " heavy-gauge, extruded solid copper pipe.

#### FINISH

Brushed Natural Copper.

(Brushed copper will rapidly age to an elegant rich bronze-like color and may develop areas of patina over time.)

### LENS:

Clear, high-impact polycarbonate lens.

### MOUNTING:

Bottom of stem fitted with 1/2" NPT Bushing.

# LED:

- Integrated LED Module. 2.5 5 Watts.
- G4 LED Lamp. 1.5 Watts.

### **ELECTRICAL:**

Input voltage range 9 - 15 VAC.

Low voltage transformer required to operate (sold separately).

## **FASTENERS:**

All fasteners are stainless steel.

### WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

### CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

# **DIMENSIONS**





