



TYPE:  MODEL:   
PROJECT:

## PRODUCT DESCRIPTION

5006 Uplight	Qty 6
GS-150 ABS Ground Stake	Qty 6
DK-250 Photocell controlled 12V Transformer & Stand (250 W)	Qty 1
Marine Grade Rolling Demonstration Case with Handle	Qty 1
10' Low Voltage Cable with Quick Connect	Qty 4
Low Voltage 3-Way Quick-Connect Splitters	Qty 4
Photocell Cap	Qty 1
Brass Thumbscrews (for securing transformer stand legs)	Qty 3



## DEMO CASE FEATURES

Housing	Injection Molded HPX™ High Performance Resin
Latches	Five Press & Pull Latches
Handles	Two Soft-grip Handles
Security	Two Padlockable Hasps
Ingress Protection Rating	IP67
Weight with Foam (no contents)	28 lbs
Dimensions	31 1/8" L x 20 1/2" W x 12 1/4" D






**5006 FEATURES**



LED Type	4.5W - 36° LED MR-16
Voltage	9 – 15 VAC
Lumens	295 Lumens
Housing	Die-cast A360 Aluminum
Finish	Black Powder Coat Finish
Lens	Clear Tempered Glass
Mounting	Injection-molded composite knuckle with 1/2" NPS thread
Dimensions	2 5/8" DIA x 5 3/4" D



**GS-150 FEATURES**



Type	Ground Stake
Material	ABS
Fixture Mounting	1/2" FPT Base
Dimensions	9" H x 2 3/8" DIA





**DK-250 FEATURES**



Wattage	250 W
Primary Voltage	120 VAC
Secondary Voltage	12 VAC
Housing	Stainless Steel
Finish	Black Powder Coat Finish

