

PRODUCT FEATURES

Wattage	150 W
Secondary Voltage	12 and 15 VAC
Housing	Stainless Steel
Dimensions	11¾" H x 6¼" W x 5¼" D





EXAMPLE: **ES-150DA**

ORDERING NOTES

descriptions:


See the following for accessory

ORDERING INFORMATION

ES

SERIES MODEL OPTIONAL FINISH

SERIES MODEL OPTIONAL FINISH ES Energy Smart Low Voltage Transformer 150 150 Watts Clear powder coat finish standard 150T 150 Watts | T timer * B Black 150DA 150 Watts | DA timer * Z Architectural Bronze 150RP 150 Watts | RP photocell * DZ Dark Bronze GT Granite







SPECIFICATIONS

HOUSING CONSTRUCTION:

20-gauge 304 stainless steel.

 $\frac{1}{2}$ "– $\frac{3}{4}$ " knockouts on each side of enclosure for conduit and accessory mounting as well as a removable, swing-down enclosure bottom with Adjustable Cable Raceway Feeder and $\frac{1}{2}$ "– $\frac{3}{4}$ " conduit knockout.

NEMA ENCLOSURE RATING:

3R

FINISH:

Clear powder coat finish standard. Also available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

TERMINALS:

- Low voltage terminal strip for multiple cable connections
- 120-volt terminal strip for easy hard-wiring and an accessory terminal strip

PRIMARY PROTECTION:

Auto thermal shut-off

SECONDARY PROTECTION:

Resettable high performance magnetic circuit breaker. Fully grounded and isolated with encapsulated core and coil.

WIRING

6-foot, heavy-gauge, grounded, water-resistant power cord with integrally molded plug.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

AVAILABLE POWER RATING:

150 Watts

PRIMARY VOLTAGE:

120 Volts

(Also available in 208V, 230V or 277V, 50 or 60 cycle - Special order only.)

SECONDARY VOLTAGE:

12 and 15 Volts

DIMENSIONS

