

TYPE:	MODEL:
PROJECT:	

PRODUCT FEATUR	ES
----------------	----

c(UL)u





Wattage	1 W
Voltage	9 – 15 VAC
Shroud	Brass, Copper or Stainless Steel
Dimensions	5%" L x 1¼" H x 4" D

ORDERING INFORMATION

EXAMPLE: **SL-4260M-B-W-LB2ND**

CATEGORY MODEL FINISH LED

SL 4260M LED

CATEGORY	MODEL	FINIS	БН			LED	
SL Step Light	4260M	В	Black	R	Rust	W-LB2ND	1 Watt Warm Integrated LED
		z	Architectural Bronze	HG	Hunter Green	C-LB2ND	1 Watt Cool Integrated LED
		DZ	Dark Bronze	WB	Weathered Bronze		
		GT	Granite	WI	Weathered Iron		
		w	White	GM	Graphite Metallic		
		BR	Architectural Brick	G	Verde		
		LZ	Light Bronze	P	Pewter		
		SB	Special Bronze	М	Mocha		
		GG	Glossy Gray	OF	Olde Finish		
		BSN	Natural Brass	CSN	Natural Copper		
		вѕо	Olde Brass	SS	Stainless Steel		



SPECIFICATIONS

SHROUD CONSTRUCTION:

Brass, Copper or Stainless Steel.

HOUSING CONSTRUCTION:

Die-cast A360 aluminum.

FINISH:

Stainless Steel shroud available with Powder coat finish in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

LENS:

Textured, high-impact polycarbonate lens.

FASTENERS:

All fasteners are stainless steel.

LED:

Integrated LED Module.

1 Watt.

ELECTRICAL:

Input voltage range 9 - 15 VAC.

Low voltage transformer required to operate (sold separately).

WIRING:

Prewired with a ten-foot pigtail of 18-2 SPT1 cable and underground connectors.

CERTIFICATIONS | STANDARDS | COMPLIANCE:

- UL Certified for wet locations (USA & Canada) | (UL 1838)
- Buy American Act (BAA)
- Build America, Buy America Act (BABA)

DIMENSIONS





