



**MODEL 2117** | Specification Sheet  
Commercial Series • Low Voltage • Underwater

TYPE:  MODEL:

PROJECT:

**PRODUCT FEATURES**



Wattage	4.5 W or 5.5 W
Voltage	9 – 15 VAC
Lumens	295 or 389 Delivered Lumens
Lamp Type	MR-16 LED
Housing	Injection-Molded Polymer
Dimensions	5" DIA x 5" D

**ORDERING INFORMATION**

EXAMPLE: **UW-2117-B-4.5-W-36-CFR**

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
UW	2117			

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
UW Underwater	2117	BSN Natural Brass BSO Olde Brass	<b>4.5-W-15</b> 4.5 Watts   Warm   15° Narrow Spot	<b>CFR</b> Crowned Frosted Lens <b>CBL</b> Crowned Cool Blue Lens <b>SL</b> Flat Spread Lens <b>DBL</b> Flat Dark Blue Lens <b>GL</b> Flat Dark Green Lens <b>RL</b> Flat Red Lens <b>YL</b> Flat Amber Lens <b>HL</b> Honeycomb louver
			<b>4.5-W-25</b> 4.5 Watts   Warm   25° Spot	
		<b>4.5-W-36</b> 4.5 Watts   Warm   36° Flood	<b>NL</b> No Lamp	
		<b>4.5-W-60</b> 4.5 Watts   Warm   60° Wide Flood		
		<b>5.5-W-15</b> 5.5 Watts   Warm   15° Narrow Spot		
		<b>5.5-W-25</b> 5.5 Watts   Warm   25° Spot		
		<b>5.5-W-36</b> 5.5 Watts   Warm   36° Flood		
		<b>5.5-W-60</b> 5.5 Watts   Warm   60° Wide Flood		
				Fixtures shipped with specified mounting hardware.



**PROFESSIONAL OUTDOOR LIGHTING**

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



## SPECIFICATIONS

### HOUSING CONSTRUCTION:

Injection-molded glass-reinforced polymer.

### LENS COVER CONSTRUCTION:

Machined Brass.

### FINISH:

Natural Brass or Olde Brass lens cover.  
Housing available in black only.

### LENS:

Clear, tempered glass lens.  
Optical effect lenses are available.

### OPTICS/AIMING:

Adjustable mounting bracket provides precise light aiming.  
Adjustable lamp bracket provides up to  $\pm 25^\circ$  of tilt. Lamp bracket can be locked into place to prevent disrupting lamp position when relamping.

### MOUNTING:

Adjustable mounting bracket mounted on a cement counter weight base for stable placement underwater.

### FASTENERS/INSERTS:

All fasteners are stainless steel with brass inserts.

### WIRING:

Pre-wired with a fifteen-foot pigtail of 18-3 submersible cable.  
Connectors for a required above-water connection are also included.

### CAUTION:

Follow installation instructions as well as local electrical codes when installing.  
**NOT** for use in swimming pools or spas.

### LED:

MR-16 LED Lamp.  
295 or 389 Lumens.  
4.5 or 5.5 Watts.

### ELECTRICAL:

Input voltage range 9 - 15 VAC.  
Low voltage transformer required to operate (sold separately).

### LIGHT DISTRIBUTION:

Very Narrow Spot **15** ( $15^\circ$ )  
Narrow Spot **25** ( $25^\circ$ )  
Medium Flood **36** ( $36^\circ$ )  
Wide Flood **60** ( $60^\circ$ )

## DIMENSIONS

