

	MODEL:			
PROJECT:				

PRODUCT FEATURES

Wattage	1 – 5 W
Voltage	9 – 15 VAC
Housing	Aluminum
Dimensions	7 %" DIA x 15 ¾" H



ORDERING INFORMATION

MOUNTING MODEL FINISH LED

PR 4704

MOUNTING	MODEL	FINISH		FINISH LED			ORDERING NOTES
PR ABS Ground Stake 4704	4704	В	Black	W-LB2ND	2.5 Watts Warm Integrated LE	Fixtures snipped with specified	
		z	Architectural Bronze	N-LB2ND	2.5 Watts Neutral Integrated LE	D mounting hardware.	
		DZ	Dark Bronze	C-LB2ND	2.5 Watts Cool Integrated LE	Custom length stems available -	
		GT	Granite	W-LB5ND	5 Watts Warm Integrated LE	D Consult local distributor.	
		w	White	N-LB5ND	5 Watts Neutral Integrated LE	D	
		BR	Architectural Brick	C-LB5ND	5 Watts Cool Integrated LE	D	
		LZ	Light Bronze	150-W-G4	1.5 Watts Warm G4 LED Lamp		
		SB	Special Bronze				
		GG	Glossy Gray	NL	No Lamp		
		R	Rust				
		HG	Hunter Green				
		WB	Weathered Bronze				
		wı	Weathered Iron				
		GM	Graphite Metallic				
		G	Verde				
		P	Pewter				
		м	Mocha				
		OF	Olde Finish				



SPECIFICATIONS

HOUSING CONSTRUCTION:

Die-cast A360 aluminum.

STEM CONSTRUCTION:

½" schedule-40 aluminum pipe.

FINISH

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

I FNS

Clear, high-impact polycarbonate lens.

MOUNTING:

Bottom of stem threaded with ½" NPT.

LED:

- Integrated LED Module. 2.5 5 Watts.
- G4 LED Lamp. 1.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.

Low voltage transformer required to operate (sold separately).

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATIONS | STANDARDS | COMPLIANCE:

- UL Certified for wet locations (USA & Canada) | (UL 1838)
- Buy American Act (BAA)
- Build America, Buy America Act (BABA)

DIMENSIONS



