

TYPE:	MODEL:
PROJECT:	

## **PRODUCT FEATURES**

c(UL)u





Wattage	1 – 5 W
Voltage	9 – 15 VAC
Housing	Aluminum
Dimensions	4¾" L x 2½" H x 3½" D



# **ORDERING INFORMATION**

EXAMPLE: **SL-4242-B-W-LB5ND** 

CATEGORY MODEL FINISH LED
SL 4242

CATEGORY	MODEL	FINISH		LED	
SL Step Light	4242	В	Black	W-LB2ND	2.5 Watts   Warm   Integrated LED
		z	Architectural Bronze	N-LB2ND	2.5 Watts   Neutral   Integrated LED
		DZ	Dark Bronze	C-LB2ND	2.5 Watts   Cool   Integrated LED
		GT	Granite	W-LB5ND	5 Watts   Warm   Integrated LED
		w	White	N-LB5ND	5 Watts   Neutral   Integrated LED
		BR	Architectural Brick	C-LB5ND	5 Watts   Cool   Integrated LED
		LZ	Light Bronze	150-W-G4	1.5 Watts   Warm   G4 LED Lamp
		SB	Special Bronze		
		GG	Glossy Gray	NL	No Lamp
		R	Rust		
		HG	Hunter Green		
		WB	Weathered Bronze		
		wı	Weathered Iron		
		GM	Graphite Metallic		
		G	Verde		
		P	Pewter		
		м	Mocha		
		OF	Olde Finish		



### **SPECIFICATIONS**

## HOUSING CONSTRUCTION:

Stamped & formed aluminum recessed box with  $\frac{1}{2}$ " knockouts on the back & side.

# COVER PLATE CONSTRUCTION:

Die-cast A360 aluminum.

#### **FINISH**

Powder coat finish for Aluminum Door Cover available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

#### LENS

Translucent, high-impact polycarbonate lens.

### MOUNTING:

Recessed mounting box included.

# LED:

- Integrated LED Module. 2.5 5 Watts.
- G4 LED Lamp. 1.5 Watts.

### **ELECTRICAL:**

Input voltage range 9 - 15 VAC.

Low voltage transformer required to operate (sold separately).

## **FASTENERS:**

All fasteners are stainless steel.

### WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

### CERTIFICATIONS | STANDARDS | COMPLIANCE:

- UL Certified for wet locations (USA & Canada) | (UL 1838)
- Buy American Act (BAA)
- Build America, Buy America Act (BABA)

# **DIMENSIONS**







