



MODEL 4260M | Specification Sheet
Commercial Series • Low Voltage • Step Light

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage 2.5 W

Voltage 9 – 15 VAC

Shroud Brass, Copper or Stainless Steel

Dimensions 5 7/8" L x 1 1/4" H x 4" D

ORDERING INFORMATION

EXAMPLE: *SL-4260M-B-W-LB2ND*

CATEGORY **MODEL** **FINISH** **LED**
SL 4260M

CATEGORY	MODEL	FINISH	LED
SL Step Light	4260M	B Black R Rust Z Architectural Bronze HG Hunter Green DZ Dark Bronze WB Weathered Bronze GT Granite WI Weathered Iron W White GM Graphite Metallic BR Architectural Brick G Verde LZ Light Bronze P Pewter SB Special Bronze M Mocha GG Glossy Gray OF Olde Finish	W-LB2ND 2.5 Watts Warm Integrated LED C-LB2ND 2.5 Watts Cool Integrated LED
		BSN Natural Brass CSN Natural Copper BSO Olde Brass SS Stainless Steel	



**PROFESSIONAL
OUTDOOR LIGHTING**

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

SHROUD CONSTRUCTION:
Brass, Copper or Stainless Steel.

HOUSING CONSTRUCTION:
Die-cast A360 aluminum.

FINISH:
Stainless Steel shroud available with Powder coat finish in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

LENS:
Textured, high-impact polycarbonate lens.

FASTENERS:
All fasteners are stainless steel.

WIRING:
Prewired with a ten-foot pigtail of 18-2 SPT1 cable and underground connectors.

CERTIFICATION:
UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:
Integrated LED Module. 2.5 Watts.

ELECTRICAL:
Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

DIMENSIONS

