



**MODEL 4243** | Specification Sheet  
Commercial Series • Low Voltage • Step Light

TYPE:  MODEL:

PROJECT:

**PRODUCT FEATURES**



Wattage	1 – 5 W
Voltage	9 – 15 VAC
Housing	Aluminum
Dimensions	3 ¼" DIA x 1 7/8" D



**ORDERING INFORMATION**

EXAMPLE: *SL-4243-B-W-LB5ND*

CATEGORY	MODEL	FINISH	LED
SL	4243		

CATEGORY	MODEL	FINISH	LED
SL Step Light	4243	<b>B</b> Black	<b>W-LB2ND</b> 2.5 Watts   Warm   Integrated LED
		<b>Z</b> Architectural Bronze	<b>N-LB2ND</b> 2.5 Watts   Neutral   Integrated LED
		<b>DZ</b> Dark Bronze	<b>C-LB2ND</b> 2.5 Watts   Cool   Integrated LED
		<b>GT</b> Granite	<b>W-LB5ND</b> 5 Watts   Warm   Integrated LED
		<b>W</b> White	<b>N-LB5ND</b> 5 Watts   Neutral   Integrated LED
		<b>BR</b> Architectural Brick	<b>C-LB5ND</b> 5 Watts   Cool   Integrated LED
		<b>LZ</b> Light Bronze	<b>1.1-W-GS-T3</b> 1.1 Watts   Warm   T3 LED Lamp
		<b>SB</b> Special Bronze	<b>NL</b> No Lamp
		<b>GG</b> Glossy Gray	
		<b>R</b> Rust	
		<b>HG</b> Hunter Green	
		<b>WB</b> Weathered Bronze	
		<b>WI</b> Weathered Iron	
		<b>GM</b> Graphite Metallic	
		<b>G</b> Verde	
<b>P</b> Pewter			
<b>M</b> Mocha			
<b>OF</b> Olde Finish			



PROFESSIONAL  
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



### SPECIFICATIONS

**HOUSING CONSTRUCTION:**

Die-cast A360 aluminum.

**FINISH:**

Powder coat finish for Aluminum Door Cover available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

**LENS:**

Frosted, tempered glass lens.

**MOUNTING:**

Surface mounting plate included.  
No recessed box required.

**FASTENERS:**

All fasteners are stainless steel.

**WIRING:**

Provided with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

**CERTIFICATIONS | STANDARDS | COMPLIANCE:**

- UL Certified for wet locations (USA & Canada) | (UL 1838)
- Buy American Act (BAA)
- Build America, Buy America Act (BABA)

**LED:**

- Integrated LED Module. 2.5 – 5 Watts.
- T3 LED Lamp. 1.1 Watts.

**ELECTRICAL:**

Input voltage range 9 - 15 VAC.  
Low voltage transformer required to operate (sold separately).

### DIMENSIONS

