



**MODEL 2114** | Specification Sheet  
Commercial Series • Low Voltage • Underwater

TYPE:  MODEL:

PROJECT:

**PRODUCT FEATURES**



Wattage	2.5 – 5 W
Voltage	9 – 15 VAC
Housing	Brass or Stainless Steel
Dimensions	2 7/8" DIA x 2 1/2" D

**ORDERING INFORMATION**

EXAMPLE: **UW-2114-BSN-W-LB5ND**

CATEGORY	MODEL	FINISH	LED
UW	2114		

CATEGORY	MODEL	FINISH	LED	ORDERING NOTES
UW Underwater	2114	BSN Natural Brass	W-LB2ND 2.5 Watts   Warm   Integrated LED	2114 <b>NOT</b> for use in swimming pools or spas.
			N-LB2ND 2.5 Watts   Neutral   Integrated LED	
		SS Stainless Steel	C-LB2ND 2.5 Watts   Cool   Integrated LED	
			W-LB5ND 5 Watts   Warm   Integrated LED	
			N-LB5ND 5 Watts   Neutral   Integrated LED	
			C-LB5ND 5 Watts   Cool   Integrated LED	





## SPECIFICATIONS

### HOUSING CONSTRUCTION:

Machined brass or stainless steel.

### LENS:

Clear, tempered soda-lime glass lens.

### FASTENERS:

All fasteners are stainless steel.

### WIRING:

Pre-wired with a fifteen-foot pigtail of 18-3 submersible cable.  
Connectors for a required above-water connection are also included.

### CERTIFICATIONS | STANDARDS | COMPLIANCE:

- Buy American Act (**BAA**)
- Build America, Buy America Act (**BABA**)

### LED:

Integrated LED Module.  
2.5 – 5 Watts.

### ELECTRICAL:

Input voltage range 9 - 15 VAC.  
Low voltage transformer required to operate (sold separately).

### CAUTION:

Follow installation instructions as well as local electrical codes when installing.  
**NOT** for use in swimming pools or spas.

## DIMENSIONS

