



**MODEL 2150** | Specification Sheet  
Commercial Series • Low Voltage • Up / Accent / Downlight

TYPE:  MODEL:

PROJECT:

**PRODUCT FEATURES**



Wattage	4.5 W or 5.5 W
Voltage	9 – 15 VAC
Lumens	295 or 389 Lumens
Lamp Type	MR-16 LED
Housing	Copper or Stainless Steel
Dimensions	2 1/8" DIA x 4 1/2" H

**ORDERING INFORMATION**

EXAMPLE: *HT-2150-CSN-4.5-W-36*

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
HT	2150			

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
HT Hanging Downlight	2150	CSN Natural Copper	4.5-W-15 4.5 Watts   Warm   15° Narrow Spot	<b>BL</b> Flat Cool Blue Lens <b>SL</b> Flat Spread Lens <b>DBL</b> Flat Dark Blue Lens <b>GL</b> Flat Dark Green Lens <b>RL</b> Flat Red Lens <b>YL</b> Flat Amber Lens <b>HL</b> Honeycomb louver
			4.5-W-25 4.5 Watts   Warm   25° Spot	
		SS Stainless Steel	4.5-W-36 4.5 Watts   Warm   36° Flood	
			4.5-W-60 4.5 Watts   Warm   60° Wide Flood	
		5.5-W-15 5.5 Watts   Warm   15° Narrow Spot	5.5-W-25 5.5 Watts   Warm   25° Spot	
			5.5-W-36 5.5 Watts   Warm   36° Flood	
		5.5-W-60 5.5 Watts   Warm   60° Wide Flood	5.5-W-60 5.5 Watts   Warm   60° Wide Flood	
			NL No Lamp	



**PROFESSIONAL  
OUTDOOR LIGHTING**

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



## SPECIFICATIONS

### CONSTRUCTION:

Heavy-gauge, extruded, copper or stainless steel fitted with machined solid brass base.

### FINISH:

Brushed Natural Copper or Stainless Steel.  
(Brushed copper will rapidly age to an elegant rich bronze-like color and may develop areas of patina over time.)

### LENS:

Clear, tempered glass lens.  
Optical effect lenses are available

### MOUNTING:

Solid brass loop with a six-foot stainless steel cable-hanger included.

### FASTENERS:

All fasteners are stainless steel.

### WIRING:

Prewired with a 36" pigtail of 18-2 SPT1 UV resistant cable and watertight connectors.

### CERTIFICATIONS | STANDARDS | COMPLIANCE:

- UL Certified for wet locations (USA & Canada) | (UL 1838)
- Buy American Act (BAA)
- Build America, Buy America Act (BABA)

### LED:

MR-16 LED Lamp.  
295 or 389 Lumens.  
4.5 or 5.5 Watts.

### ELECTRICAL:

Input voltage range 9 - 15 VAC.  
Low voltage transformer required to operate (sold separately).

## DIMENSIONS

