



MODEL 2146 | Specification Sheet

Commercial Series • Low Voltage • Step Light

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	5 W Max.
Voltage	9 – 15 VAC
Faceplate	Brass, Copper or Stainless Steel
Dimensions	9 1/8" L x 2 7/8" H x 3 1/2" D

ORDERING INFORMATION

EXAMPLE: SL-2146-BSN-W-LC5ND

CATEGORY	MODEL	FINISH	LED
SL	2146		
SL Step Light	2146	BSN Natural Brass	W-LC5ND 4 Watts Warm Integrated LED
		BSO Olde Brass	N-LC5ND 4 Watts Neutral Integrated LED
		CSN Natural Copper	C-LC5ND 4 Watts Cool Integrated LED
		CSO Olde Copper	150-W-G4 1.5 Watts Warm G4 LED Lamp (x 2)
		SS Stainless Steel	
		Also available in 18 standard powder coat finishes. See specifications on pg. 2 for description and order codes.	NL No Lamp



PROFESSIONAL
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)
Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Stamped & formed aluminum recessed box with ½" knockouts on the back & side.

COVER PLATE CONSTRUCTION:

Stamped solid brass, copper, or stainless steel.

FINISH:

Brushed Natural Copper, Natural Brass, Olde Copper finish, Olde Brass finish or Stainless Steel.

(Brushed copper will rapidly age to an elegant rich bronze-like color and may develop areas of patina over time.)

Also available in powder coat finish with the following standard colors:

Black (**B**), Architectural Bronze (**Z**), Dark Bronze (**DZ**), Granite (**GT**), White (**W**), Architectural Brick (**BR**), Light Bronze (**LZ**), Special Bronze (**SB**), Glossy Gray (**GG**), Rust (**R**), Hunter Green (**HG**), Weathered Bronze (**WB**), Weathered Iron (**WI**), Graphite Metallic (**GM**), Verde (**G**), Pewter (**P**), Mocha (**M**) and Olde Finish (**OF**).

LENS:

Translucent, high-impact polycarbonate lens.

MOUNTING:

Recessed mounting box included.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATIONS | STANDARDS | COMPLIANCE:

- UL Certified for wet locations (USA & Canada) | (**UL 1838**)
- Buy American Act (**BAA**)
- Build America, Buy America Act (**BABA**)

LED:

- Integrated LED Module. 2 – 4 Watts.
- G4 LED Lamp (x 2). 1.5 Watts (x 2).

ELECTRICAL:

Input voltage range 9 - 15 VAC.

Low voltage transformer required to operate (sold separately).

DIMENSIONS

