



MODEL 1059 | Specification Sheet

Commercial Series • Floodlight • LED

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	48 – 113 W
Voltage	120 – 277 VAC
Lumens	2460 – 10,700 Delivered Lumens
Distribution	NEMA type [H x V]: 2x2 (VNS), 2x2 (NS), 5x5 (MF), 6x6 (WF)
CCT	2700K, 3000K, 3500K, 4000K, 5000K
CRI	80 CRI min.
Dimming	0-10V or Phase Cut (TRIAC/ELV-120VAC only) available
Driver	Multi-Volt 120-277VAC with tri-modal dimming capabilities
Dimensions	10 $\frac{1}{8}$ " W x 12 $\frac{15}{16}$ " D x 9" DIA



ORDERING INFORMATION

EXAMPLE: 1059-GM-WF-27-D-MV-PCT-FS

MODEL	FINISH	DISTRIBUTION	COLOR TEMP	LUMENS	VOLTAGE	DIMMING	ACCESSORIES		
1059					MV				
MODEL	FINISH	DISTRIBUTION	COLOR TEMP	DELIVERED LUMENS	VOLTAGE	DIMMING	ACCESSORIES		
1059	B Black	VNS Very Narrow Spot	27 2700K	B 2460 Lumens	MV Multi Volt	ND Non Dimming	BD Barn Doors		
	Z Architectural Bronze			C 2793 Lumens					
	DZ Dark Bronze								
	GT Granite		30 3000K 35 3500K 40 4000K 50 5000K	B 2460 Lumens		010 0-10V	FS Full Light Shield		
	W White			C 2793 Lumens					
	BR Architectural Brick			H 5887 Lumens					
	LZ Light Bronze			I 6416 Lumens					
	SB Special Bronze								
	GG Glossy Gray	NS Narrow Spot	27 2700K	D 3199-3559 Lumens		PCT Phase Cut	HS Half Light Shield		
	R Rust			E 3476-3874 Lumens					
	HG Hunter Green			F 3933-4281 Lumens					
	WB Weathered Bronze	MF Medium Flood	30 3000K 35 3500K 40 4000K 50 5000K	G 4566-5181 Lumens			DF Diffuse Filter		
	WI Weathered Iron			D 3199-3559 Lumens					
	GM Graphite Metallic			E 3476-3874 Lumens					
	G Verde	WF Wide Flood	30 3000K 35 3500K 40 4000K 50 5000K	F 3933-4281 Lumens			LSFH Linear Spread Filter Horizontal LSFV Linear Spread Filter Vertical		
	P Pewter			G 4566-5181 Lumens					
	M Mocha			H 9333-9550 Lumens					
	OF Olde Finish			I 10,301-10,708 Lumens					



PROFESSIONAL
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)
Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING:

Die-cast A360 aluminum. Optic and driver compartment environmentally sealed. Housing aiming achieved via a heavy aluminum yoke strap and locked in position with stainless steel lock washers and nuts. Locking fasteners are covered with decorative die-cast aluminum end caps.

DOOR:

Die-cast A360 aluminum. Stainless steel fasteners. Door is designed to shed water from the lens surface.

FINISH:

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish. Custom Powder coat finishes available on request.

LENS:

¼" thick tempered and beveled clear glass.

REFLECTOR:

Specular, semi-specular, or White Optic coated spun reflectors, anodized for maximum performance. Very Narrow Spot optic incorporates an additional internal source shield to eliminate unwanted glare outside the beam pattern.

LED:

Performance COB LEDs powered from 1050mA-2000mA.
2460 – 10,700 Lumens delivered.
48 – 113 Watts.

COLOR TEMPERATURE:

2700K, 3000K, 3500K, 4000K or 5000K CCT White.

COLOR RENDERING:

80 CRI minimum

OPTICS/AIMING:

ACCESSORIES:

Barn Doors, Full Shield, Half Shield, Diffuse Filter and Linear Spread Filter available.

WIRING:

- 18/3 SEOWW outdoor rated waterproof cable
[for Non-dimmable and Phase Cut (TRIAC/ELV-120VAC only) options]
- 18/5 SJTOW outdoor rated waterproof cable
[for 0-10V dimming option]

Cable exits fixture housing through a liquid tight cable fitting.

MOUNTING:

Yoke provided with ½ NPSM stainless Cord Seal Mount to secure the yoke strap directly into a ½-14 NPT threaded opening. See the Vista website for additional Mounts and Accessories.

CERTIFICATION:

cULus wet location listed.
Ingress Protection Rating: IP66

NEMA defined floodlight optics.

Housing aiming achieved via an aluminum yoke strap.


DRIVER:

Multi-Volt **MV** 120V-277V equipped with tri-modal dimming capabilities.
Start up/Operating Temperature: -10°C to +50°C.
Non-dimmable, 0-10V and Phase Cut (TRIAC/ELV-120VAC only) options available.

LIGHT DISTRIBUTION:

Very Narrow Spot **VNS** (NEMA 2H x 2V), Narrow Spot **NS** (NEMA 2H x 2V),
Medium Flood **MF** (NEMA 5H x 5V), Wide Flood **WF** (NEMA 6H x 6V)

DIMENSIONS





DELIVERED LUMENS

LUMEN PACKAGE	VNS	NS	MF	WF
B	60 Watts 2460 Lumens			
C	74 Watts 2793 Lumens			
D		48 Watts 3559 Lumens	48 Watts 3407 Lumens	48 Watts 3199 Lumens
E		50 Watts 3874 Lumens	50 Watts 3744 Lumens	49 Watts 3476 Lumens
F		60 Watts 4281 Lumens	60 Watts 4151 Lumens	59 Watts 3933 Lumens
G		74 Watts 5181 Lumens	74 Watts 4972 Lumens	74 Watts 4566 Lumens
H	96 Watts 5887 Lumens	96 Watts 9333 Lumens	96 Watts 9550 Lumens	95 Watts 9340 Lumens
I	112 Watts 6416 Lumens	113 Watts 10,360 Lumens	113 Watts 10,708 Lumens	112 Watts 10,301 Lumens

