

TYPE:	MODEL:

PRODUCT	FEATU	IRES
---------	-------	------



Wattage	2.5 – 5 W
Voltage	9 – 15 VAC
Housing	Brass or Stainless Steel
Dimensions	2%" DIA x 2½" D

ORDERING INFORMATION

EXAMPLE: UW-2114-BSN-W-LB5ND

CATEGORY MODEL FINISH LED
UW 2114

CATEGORY	MODEL	FINISH	LED	ORDERING NOTES
UW Underwater	2114	BSN Natural Brass	W-LB2ND 2.5 Watts Warm Integrated LED	2114 NOT for use in swimming
		SS Stainless Steel	N-LB2ND 2.5 Watts Neutral Integrated LED	pools or spas.
			C-LB2ND 2.5 Watts Cool Integrated LED	
			W-LB5ND 5 Watts Warm Integrated LED	
			N-LB5ND 5 Watts Neutral Integrated LED	
			C-LB5ND 5 Watts Cool Integrated LED	
	<u> </u>	<u> </u>		<u> </u>



SPECIFICATIONS

HOUSING CONSTRUCTION:

Machined brass or stainless steel.

LENS:

Clear, tempered soda-lime glass lens.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Pre-wired with a fifteen-foot pigtail of 18-3 submersible cable.

Connectors for a required above-water connection are also included.

LED:

Integrated LED Module. 2.5 – 5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.

Low voltage transformer required to operate (sold separately).

CAUTION:

Follow installation instructions as well as local electrical codes when installing.

 $\ensuremath{\text{NOT}}$ for use in swimming pools or spas.

DIMENSIONS



