



MODEL 2118 | Specification Sheet

Commercial Series • Low Voltage • Underwater

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	5 W
Voltage	9 – 15 VAC
CCT	3000K (WARM) 4000K (NEUTRAL) 5000K (COOL)
Housing	Brass or Stainless Steel
Dimensions	2 7/8" DIA x 2 1/2" D

ORDERING INFORMATION

EXAMPLE: UW-2118-BSN-W-LC5ND

CATEGORY	MODEL	FINISH	LED
UW	2118		

CATEGORY	MODEL	FINISH	LED	ORDERING NOTES
UW Underwater	2118	BSN Natural Brass SS Stainless Steel Also available in 18 standard powder coat finishes. See specifications on pg. 2 for description and order codes.	W-LC5ND 5 Watts Warm Integrated LED N-LC5ND 5 Watts Neutral Integrated LED C-LC5ND 5 Watts Cool Integrated LED	2118 NOT for use in swimming pools or spas.



PROFESSIONAL
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)
Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Machined brass or stainless steel.

FINISH:

Natural Brass or Stainless Steel.

Also available in powder coat finish with the following standard colors:

Black (**B**), Architectural Bronze (**Z**), Dark Bronze (**DZ**), Granite (**GT**), White (**W**), Architectural Brick (**BR**), Light Bronze (**LZ**), Special Bronze (**SB**), Glossy Gray (**GG**), Rust (**R**), Hunter Green (**HG**), Weathered Bronze (**WB**), Weathered Iron (**WI**), Graphite Metallic (**GM**), Verde (**G**), Pewter (**P**), Mocha (**M**) and Olde Finish (**OF**).

LENS:

Clear, tempered soda-lime glass lens.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Pre-wired with a fifteen-foot pigtail of 18-3 submersible cable.
Connectors for a required above-water connection are also included.

CERTIFICATIONS | STANDARDS | COMPLIANCE:

- Buy American Act (**BAA**)
- Build America, Buy America Act (**BABA**)

LED:

Integrated LED Module.
5 Watts.

COLOR TEMPERATURE:

3000K, 4000K or 5000K CCT White.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

CAUTION:

Follow installation instructions as well as local electrical codes when installing.

NOT for use in swimming pools or spas.

DIMENSIONS

