



PHOTOMETRIC TEST SUMMARY

1182

| FILE NO. | MODEL NAME | DISTRIBUTION | NEMA TYPE | BEAM ANGLE | FIELD ANGLE | MAX CANDELA | TOTAL LUMENS | WATTAGE | EFFICACY | CRI | CCT |
|------------|---------------|------------------|-----------|------------|-------------|-------------|--------------|---------|----------|-----|------|
| L022011607 | 1182-VNS-B-CX | Very Narrow Spot | 1H x 1V | 9° | 16° | 9832 | 287 | 6.4 | 45 | 84 | 2931 |
| L022011608 | 1182-VNS-C-CX | Very Narrow Spot | 1H x 1V | 9° | 16° | 16883 | 511 | 10.0 | 51 | 83 | 2962 |
| L022011609 | 1182-VNS-D-CX | Very Narrow Spot | 1H x 1V | 9° | 16° | 19688 | 588 | 11.7 | 50 | 83 | 2990 |
| L091910603 | 1182-VNS-E-CX | Very Narrow Spot | 1H x 1V | 9° | 16° | 21121 | 646 | 13.9 | 47 | 84 | 2962 |
| L022011604 | 1182-NS-B-CX | Narrow Spot | 1H x 1V | 9° | 16° | 12917 | 455 | 6.3 | 72 | 84 | 2906 |
| L022011605 | 1182-NS-C-CX | Narrow Spot | 1H x 1V | 9° | 16° | 22007 | 777 | 9.9 | 78 | 83 | 2943 |
| L022011606 | 1182-NS-D-CX | Narrow Spot | 1H x 1V | 9° | 16° | 26131 | 912 | 11.7 | 78 | 83 | 2972 |
| L121800903 | 1182-NS-E-CX | Narrow Spot | 1H x 1V | 10° | 17° | 29669 | 1093 | 13.8 | 79 | 83 | 2914 |
| L022011601 | 1182-MF-B-CX | Medium Flood | 4H x 4V | 38° | 63° | 1266 | 564 | 6.3 | 90 | 84 | 2894 |
| L022011602 | 1182-MF-C-CX | Medium Flood | 4H x 4V | 39° | 65° | 1949 | 908 | 9.8 | 92 | 83 | 2943 |
| L022011603 | 1182-MF-D-CX | Medium Flood | 4H x 4V | 39° | 66° | 2184 | 1043 | 11.6 | 90 | 83 | 2978 |
| L121800904 | 1182-MF-E-CX | Medium Flood | 4H x 4V | 39° | 63° | 2642 | 1241 | 13.9 | 90 | 84 | 2919 |
| L061910603 | 1182-WF-B-CX | Wide Flood | 5H x 5V | 54° | 82° | 727 | 570 | 6.3 | 91 | 85 | 2889 |
| L091910601 | 1182-WF-C-CX | Wide Flood | 5H x 5V | 53° | 82° | 1169 | 904 | 9.8 | 93 | 84 | 2940 |
| L091910602 | 1182-WF-D-CX | Wide Flood | 5H x 5V | 54° | 79° | 1396 | 1084 | 11.5 | 94 | 84 | 2980 |
| L121800905 | 1182-WF-E-CX | Wide Flood | 5H x 5V | 55° | 81° | 1630 | 1301 | 14.0 | 93 | 84 | 2925 |