



PHOTOMETRIC TEST SUMMARY

1051 | RGBW

FILE NO.	MODEL NAME	DISTRIBUTION	COLOR OUTPUT	H. BEAM ANGLE	V. BEAM ANGLE	NEMA TYPE	MAX. CANDELA	MAX. CANDELA ANGLE	TOTAL LUMENS	WATTAGE	EFFICACY	CCT	CRI
L052510701	1051-NS-RGBW-(R)	Narrow Spot	Red	91°	29°	7H x 6V	201	-5H 0V	222	8.3	27	N.A.	N.A.
L052510702	1051-NS-RGBW-(G)	Narrow Spot	Green	87°	29°	7H x 6V	480	-3H 0V	528	11.6	46	N.A.	N.A.
L052510703	1051-NS-RGBW-(B)	Narrow Spot	Blue	89°	31°	7H x 6V	104	-3H 0V	119	11.3	11	N.A.	N.A.
L052510704	1051-NS-RGBW-(W)	Narrow Spot	White	88°	28°	7H x 6V	2173	-3H 0V	2303	34.0	68	3190	90
80239581-5	1051-MF-RGBW-(R)	Medium Flood	Red	92°	62°	7H x 5V	168	-1H -13V	262	8.5	31	N.A.	N.A.
80239581-6	1051-MF-RGBW-(G)	Medium Flood	Green	98°	63°	7H x 5V	386	0H -11V	643	11.9	54	N.A.	N.A.
80239581-7	1051-MF-RGBW-(B)	Medium Flood	Blue	95°	62°	7H x 5V	90	-1H -13V	146	11.6	13	N.A.	N.A.
L052510708	1051-MF-RGBW-(W)	Medium Flood	White	95°	57°	7H x 5V	1537	0H -7V	2281	34.0	67	3190	90
L052510709	1051-WF-RGBW-(R)	Wide Flood	Red	80°	91°	7H x 7V	113	-1H -19.5V	248	8.6	29	N.A.	N.A.
L052510710	1051-WF-RGBW-(G)	Wide Flood	Green	80°	91°	7H x 7V	263	0H -19.5V	580	11.6	50	N.A.	N.A.
L052510711	1051-WF-RGBW-(B)	Wide Flood	Blue	79°	91°	7H x 7V	71	0H -19.5V	155	11.7	13	N.A.	N.A.
L052510712	1051-WF-RGBW-(W)	Wide Flood	White	78°	88°	7H x 7V	1070	-1H -19.5V	2287	34.0	67	3190	90
L052510713	1051-WW-RGBW-(R)	Wall Wash	Red	84°	52°	7H x 7V	150	-5H 25.5V	257	8.6	30	N.A.	N.A.
L052510714	1051-WW-RGBW-(G)	Wall Wash	Green	83°	53°	7H x 7V	347	-3H 25.5V	597	11.7	51	N.A.	N.A.
L052510715	1051-WW-RGBW-(B)	Wall Wash	Blue	84°	54°	7H x 7V	91	-3H 25.5V	157	11.9	13	N.A.	N.A.
L052510716	1051-WW-RGBW-(W)	Wall Wash	White	84°	51°	7H x 7V	1419	-1H 25.5V	2356	34.0	69	3190	90
L052510717	1051-WG-RGBW-(R)	Wall Grazer	Red	102°	34°	7H x 4V	332	0H 5V	301	8.6	35	N.A.	N.A.
L052510718	1051-WG-RGBW-(G)	Wall Grazer	Green	103°	36°	7H x 4V	761	0H 5V	714	11.7	61	N.A.	N.A.
L052510719	1051-WG-RGBW-(B)	Wall Grazer	Blue	101°	37°	7H x 4V	205	-1H 5V	191	11.7	16	N.A.	N.A.
L052510720	1051-WG-RGBW-(W)	Wall Grazer	White	101°	21°	7H x 4V	3501	-3H 7V	2546	34.0	75	3190	90
L052510721	1051-AS-RGBW-(R)	Asymmetric	Red	96°	69°	7H x 6V	148	-3H 29V	254	8.1	31	N.A.	N.A.
L052510722	1051-AS-RGBW-(G)	Asymmetric	Green	95°	69°	7H x 6V	355	7H 33V	604	11.5	53	N.A.	N.A.
L052510723	1051-AS-RGBW-(B)	Asymmetric	Blue	93°	68°	7H x 6V	81	-15H 29V	136	11.2	12	N.A.	N.A.
L052510724	1051-AS-RGBW-(W)	Asymmetric	White	92°	67°	7H x 6V	1472	0H 37.5V	2510	34.0	74	3190	90