



# MODEL 2116 | Specification Sheet

Commercial Series • Low Voltage • Up / Accent / Downlight

TYPE:  MODEL:

PROJECT:

## PRODUCT FEATURES



Wattage	4.5 W or 5.5 W
Voltage	9 – 15 VAC
Lumens	295 or 389 Lumens
Lamp Type	MR-16 LED
Housing	Copper, Brass or Stainless Steel
Dimensions	2 1/8" DIA x 7 3/8" D

## ORDERING INFORMATION

EXAMPLE: GR-2116-CSN-4.5-W-36-FR

CATEGORY	MODEL	FINISH	LED
	2116		

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
<b>GR</b> ABS Ground Stake <b>WB</b> Brass Wall-Mount Canopy	<b>2116</b>	<b>CSN</b> Natural Copper <b>CSO</b> Olde Copper <b>BSN</b> Natural Brass <b>SS</b> Stainless Steel  Also available in 18 standard powder coat finishes. See specifications on pg. 2 for description and order codes.	<b>4.5-W-15</b> 4.5 Watts   Warm   15° Narrow Spot <b>4.5-W-25</b> 4.5 Watts   Warm   25° Spot <b>4.5-W-36</b> 4.5 Watts   Warm   36° Flood <b>4.5-W-60</b> 4.5 Watts   Warm   60° Wide Flood  <b>5.5-W-15</b> 5.5 Watts   Warm   15° Narrow Spot <b>5.5-W-25</b> 5.5 Watts   Warm   25° Spot <b>5.5-W-36</b> 5.5 Watts   Warm   36° Flood <b>5.5-W-60</b> 5.5 Watts   Warm   60° Wide Flood  <b>NL</b> No Lamp	<b>BL</b> Flat Cool Blue Lens <b>SL</b> Flat Spread Lens <b>DBL</b> Flat Dark Blue Lens <b>GL</b> Flat Dark Green Lens  <b>RL</b> Flat Red Lens <b>YL</b> Flat Amber Lens <b>HL</b> Honeycomb louver



PROFESSIONAL  
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)  
Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



## SPECIFICATIONS

### CONSTRUCTION:

Heavy-gauge, extruded, copper, brass or stainless steel with machined brass base.

### FINISH:

Brushed Natural Copper, Natural Brass, Olde Copper finish or Stainless Steel.  
(Brushed copper will rapidly age to an elegant rich bronze-like color and may develop areas of patina over time.)

Also available in powder coat finish with the following standard colors:

Black (**B**), Architectural Bronze (**Z**), Dark Bronze (**DZ**), Granite (**GT**), White (**W**),  
Architectural Brick (**BR**), Light Bronze (**LZ**), Special Bronze (**SB**), Glossy Gray (**GG**),  
Rust (**R**), Hunter Green (**HG**), Weathered Bronze (**WB**), Weathered Iron (**WI**),  
Graphite Metallic (**GM**), Verde (**G**), Pewter (**P**), Mocha (**M**) and Olde Finish (**OF**).

### LENS:

Clear, tempered glass lens.  
Optical effect lenses are available.

### LED:

MR-16 LED Lamp.  
295 or 389 Lumens.  
4.5 or 5.5 Watts.

### ELECTRICAL:

Input voltage range 9 - 15 VAC.  
Low voltage transformer required to operate (sold separately).

### MOUNTING:

Solid Brass knuckle with 1/2" NPS thread.

### FASTENERS/INSERTS:

Fasteners are stainless steel and brass.

### WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

### CERTIFICATIONS | STANDARDS | COMPLIANCE:

- UL Certified for wet locations (USA & Canada) | (**UL 1838**)
- Buy American Act (**BAA**)
- Build America, Buy America Act (**BABA**)

## DIMENSIONS

