



PHOTOMETRIC TEST SUMMARY

1054 | RGBW

FILE NO.	MODEL NAME	DISTRIBUTION	COLOR OUTPUT	H. BEAM ANGLE	V. BEAM ANGLE	NEMA TYPE	MAX. CANDELA	MAX. CANDELA ANGLE	TOTAL LUMENS	WATTAGE	EFFICACY	CCT	CRI
L052510749	1054-NS-RGBW-(R)	Narrow Spot	Red	91°	29°	7H x 6V	718	-5H 0V	791	29.7	27	N.A.	N.A.
L052510750	1054-NS-RGBW-(G)	Narrow Spot	Green	87°	29°	7H x 6V	1717	-1H 0V	1884	41.3	46	N.A.	N.A.
L052510751	1054-NS-RGBW-(B)	Narrow Spot	Blue	89°	31°	7H x 6V	370	-3H 0V	426	40.2	11	N.A.	N.A.
L052510752	1054-NS-RGBW-(W)	Narrow Spot	White	88°	28°	7H x 6V	6121	-3H 0V	6489	96	68	3190	90
80239581-53	1054-MF-RGBW-(R)	Medium Flood	Red	94°	61°	7H x 5V	654	0H 15V	1009	30	34	N.A.	N.A.
80239581-54	1054-MF-RGBW-(G)	Medium Flood	Green	98°	63°	7H x 5V	1484	0H -11V	2473	42	59	N.A.	N.A.
80239581-55	1054-MF-RGBW-(B)	Medium Flood	Blue	96°	62°	7H x 5V	348	-1H -11V	562	41	14	N.A.	N.A.
80239581-56	1054-MF-RGBW-(W)	Medium Flood	White	95°	57°	7H x 5V	3521	0H -7V	8271	98	85	3190	90
L052510757	1054-WF-RGBW-(R)	Wide Flood	Red	80°	91°	7H x 7V	402	-1H -19.5V	884	31	29	N.A.	N.A.
L052510758	1054-WF-RGBW-(G)	Wide Flood	Green	80°	91°	7H x 7V	937	0H -19.5V	2073	42	50	N.A.	N.A.
L052510759	1054-WF-RGBW-(B)	Wide Flood	Blue	79°	91°	7H x 7V	252	0H -19.5V	553	42	13	N.A.	N.A.
L052510760	1054-WF-RGBW-(W)	Wide Flood	White	78°	88°	7H x 7V	3102	-1H -19.5V	6630	99	67	3190	90
L052510761	1054-WW-RGBW-(R)	Wall Wash	Red	82°	52°	7H x 7V	536	-1H 25.5V	916	31	30	N.A.	N.A.
L052510762	1054-WW-RGBW-(G)	Wall Wash	Green	83°	53°	7H x 7V	1240	-1H 25.5V	2131	42	51	N.A.	N.A.
L052510763	1054-WW-RGBW-(B)	Wall Wash	Blue	83°	54°	7H x 7V	325	-3H 25.5V	562	43	13	N.A.	N.A.
L052510764	1054-WW-RGBW-(W)	Wall Wash	White	84°	51°	7H x 7V	4176	0H 25.5V	6930	99	70	3190	90
L052510765	1054-WG-RGBW-(R)	Wall Grazer	Red	102°	34°	7H x 4V	1184	0H 5V	1073	31	35	N.A.	N.A.
L052510766	1054-WG-RGBW-(G)	Wall Grazer	Green	103°	36°	7H x 4V	2718	0H 5V	2550	42	61	N.A.	N.A.
L052510767	1054-WG-RGBW-(B)	Wall Grazer	Blue	101°	37°	7H x 4V	732	0H 5V	680	42	16	N.A.	N.A.
L052510768	1054-WG-RGBW-(W)	Wall Grazer	White	101°	21°	7H x 4V	11481	-3H 7V	8346	100	84	3190	90
L052510769	1054-AS-RGBW-(R)	Asymmetric	Red	96°	69°	7H x 6V	528	-1H 33V	908	29	31	N.A.	N.A.
L052510770	1054-AS-RGBW-(G)	Asymmetric	Green	95°	69°	7H x 6V	1267	7H 33V	2157	41	53	N.A.	N.A.
L052510771	1054-AS-RGBW-(B)	Asymmetric	Blue	94°	68°	7H x 6V	288	-15H 29V	485	41	12	N.A.	N.A.
L052510772	1054-AS-RGBW-(W)	Asymmetric	White	92°	67°	7H x 6V	4146	0H 37.5V	7069	96	74	3190	90