



# MODEL 1451 | Specification Sheet

Commercial Series • Bollard

TYPE:  MODEL:

PROJECT:

## PRODUCT FEATURES

Wattage	75 W maximum
Voltage	120 VAC
Lamp Type	A19 compatible (lamp not included)
Dimensions	10" DIA x 33 1/4" H



## ORDERING INFORMATION

EXAMPLE: 1451-B-CR

MODEL	FINISH	LENS
1451		

MODEL	FINISH	LENS
1451	<b>B</b> Black	<b>CR</b> Clear Lens <b>FR</b> Frosted Lens <b>PR</b> Prismatic Lens
	<b>Z</b> Architectural Bronze	
	<b>DZ</b> Dark Bronze	
	<b>GT</b> Granite	
	<b>W</b> White	
	<b>BR</b> Architectural Brick	
	<b>LZ</b> Light Bronze	
	<b>SB</b> Special Bronze	
	<b>GG</b> Glossy Gray	
	<b>R</b> Rust	
	<b>HG</b> Hunter Green	
	<b>WB</b> Weathered Bronze	
	<b>WI</b> Weathered Iron	
	<b>GM</b> Graphite Metallic	
	<b>G</b> Verde	
	<b>P</b> Pewter	
	<b>M</b> Mocha	
	<b>OF</b> Olde Finish	



PROFESSIONAL  
OUTDOOR LIGHTING



## SPECIFICATIONS

### HOUSING CONSTRUCTION:

Die-cast A360 aluminum.

### POST CONSTRUCTION:

3" Diameter, heavy gauge, extruded aluminum ( $\frac{1}{8}$ " wall thickness).

### FINISH:

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

### LAMP TYPE:

A19 compatible. Lamp not included.

### LENS:

Tempered glass lens. Clear, Frosted or Prismatic available.

### MOUNTING:

Direct-burial post. (Post extended 12" for in-ground or concrete mounting.)

### FASTENERS:

All fasteners are stainless steel.

### WIRING:

Prewired with 150° C-rated wire.

### CERTIFICATIONS | STANDARDS | COMPLIANCE:

- UL Certified for wet locations (USA & Canada) | (UL 1598)
- Buy American Act (BAA)
- Build America, Buy America Act (BABA)

## DIMENSIONS

