



8165 E. Kaiser Blvd. Anaheim, CA 92808

www.lightlaboratory.com

Photometric Test Report

IES FLOOD REPORT

PHOTOMETRIC FILENAME : L112310582.IES

DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] L112310582

[TESTLAB] LIGHT LABORATORY, INC. (www.lightlaboratory.com)

[ISSUE DATE] 4/10/2024

[MANUFAC] USTE dba Vista Professional Outdoor Lighting

[LUMCAT] 1043-WF-RGBW-(R)

[LUMINAIRE] 1043 (Accent), Wide Flood, Red output

[BALLASTCAT] eldoLED PW50S-M4Z0X1, QTY:1

[OTHER] INDICATING THE CANDELA VALUES ARE ABSOLUTE AND
[MORE] SHOULD NOT BE FACTORED FOR DIFFERENT LAMP RATINGS.

[INPUT] 120VAC

[TEST PROCEDURE] IESNA:LM-79-19

Note: Candela values converted from Type-C to Type-B

CHARACTERISTICS


NEMA Type	5 H x 5 V
Maximum Candela	92
Maximum Candela Angle	0H 0V
Horizontal Beam Angle (50%)	55.5
Vertical Beam Angle (50%)	55.5
Horizontal Field Angle (10%)	94.6
Vertical Field Angle (10%)	94.6
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Beam Lumens	50
Beam Efficiency	N.A.
Field Lumens	78
Field Efficiency	N.A.
Spill Lumens	15
Luminaire Lumens	93
Total Efficiency	N.A.
Total Luminaire Watts	10.41
Ballast Factor	1.00

IES FLOOD REPORT
PHOTOMETRIC FILENAME : L112310582.IES

AXIAL CANDELA


DEG.	HOR.	DEG.	VERT.
90	0	90	0
85	2	85	2
75	2	75	2
65	4	65	4
55	6	55	6
47.5	9	47.5	9
42.5	14	42.5	14
37.5	22	37.5	22
33	31	33	31
29	42	29	42
25.5	53	25.5	53
22.5	61	22.5	61
19.5	68	19.5	68
17	73	17	73
15	77	15	77
13	81	13	81
11	83	11	83
9	86	9	86
7	88	7	88
5	90	5	90
3	91	3	91
1	91	1	91
0	92	0	92
-1	91	-1	91
-3	91	-3	91
-5	90	-5	90
-7	88	-7	88
-9	86	-9	86
-11	83	-11	83
-13	81	-13	81
-15	77	-15	77
-17	73	-17	73
-19.5	68	-19.5	68
-22.5	61	-22.5	61
-25.5	53	-25.5	53
-29	42	-29	42
-33	31	-33	31
-37.5	22	-37.5	22
-42.5	14	-42.5	14
-47.5	9	-47.5	9
-55	6	-55	6
-65	4	-65	4
-75	2	-75	2
-85	2	-85	2
-90	0	-90	0

AXIAL CANDELA DISPLAY



Maximum Candela = 92 Located At Horizontal Angle = 0, Vertical Angle = 0
H - Horizontal Axial Candela
V - Vertical Axial Candela

ISOCANDELA CURVES



Maximum Candela = 92 Located At Horizontal Angle = 0, Vertical Angle = 0
50% Maximum Candela = 46
10% Maximum Candela = 9.2