TYPE:	MODEL:
PROJECT:	

PRODUCT FEATURES

c(UL)u





Wattage	9 W Max.
Voltage	9 – 15 VAC
Lumens	295 or 389 Lumens
Lamp Туре	MR-16 LED
Housing	Brass
Dimensions	2½" DIA x 6¾" D

ORDERING INFORMATION

EXAMPLE: GR-2350-BSN-4.5-W-36-FR

CATEGORY MODEL		MODEL	FINISH		LED		ACCESSORIES	
GR	ABS Ground Stake	2350	BSN	Natural Brass	4.5-W-15	4.5 Watts Warm 15° Narrow Spot	BL	Flat Cool Blue Lens
WB	Brass Wall-Mount Canopy		BSO	Olde Brass	4.5-W-25	4.5 Watts Warm 25° Spot	SL	Flat Spread Lens
					4.5-W-36	4.5 Watts Warm 36° Flood	DBL	Flat Dark Blue Lens
					4.5-W-60	4.5 Watts Warm 60° Wide Flood	GL	Flat Dark Green Lens
					5.5-W-15	5.5 Watts Warm 15° Narrow Spot	RL	Flat Red Lens
					5.5-W-25	5.5 Watts Warm 25° Spot	YL	Flat Amber Lens
					5.5-W-36	5.5 Watts Warm 36° Flood	HL	Honeycomb louver
					5.5-W-60	5.5 Watts Warm 60° Wide Flood		
					NL	No Lamp		



SPECIFICATIONS

HOUSING CONSTRUCTION:

Solid Brass.

FINISH:

Natural Brass or Olde Brass.

LENS:

Clear, tempered glass lens. Optical effect lenses are available.

MOUNTING:

Solid Brass knuckle with ½" NPS thread.

FASTENERS/INSERTS:

Fasteners are stainless steel and brass.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATIONS | STANDARDS | COMPLIANCE:

- UL Certified for wet locations (USA & Canada) | (UL 1838)
- Buy American Act (BAA)
- Build America, Buy America Act (BABA)

LED:

MR-16 LED Lamp. 295 or 389 Lumens. 4.5 or 5.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC. Low voltage transformer required to operate (sold separately).

DIMENSIONS



