



MODEL 2150-P | Specification Sheet
Commercial Series • Low Voltage • Up / Accent / Downlight

TYPE: MODEL:
PROJECT:

PRODUCT FEATURES



| | |
|------------|---------------------------|
| Wattage | 4.5 W or 5.5 W |
| Voltage | 9 – 15 VAC |
| Lumens | 295 or 389 Lumens |
| Lamp Type | MR-16 LED |
| Housing | Copper or Stainless Steel |
| Dimensions | 2 1/8" DIA x 6 5/8" H |

ORDERING INFORMATION

EXAMPLE: HT-2150-CSN-4.5-W-36

| CATEGORY | MODEL | FINISH | LED | ACCESSORIES |
|----------|-------|--------|-----|-------------|
| HT | 2150 | | | |

| CATEGORY | MODEL | FINISH | LED | ACCESSORIES |
|----------------------|-------|---|---|---|
| HT Hanging Downlight | 2150 | CSN-P Perforated Natural Copper | 4.5-W-15 4.5 Watts Warm 15° Narrow Spot | BL Flat Cool Blue Lens SL Flat Spread Lens DBL Flat Dark Blue Lens GL Flat Dark Green Lens RL Flat Red Lens YL Flat Amber Lens HL Honeycomb louver |
| | | | 4.5-W-25 4.5 Watts Warm 25° Spot | |
| | | SS-P Perforated Stainless Steel | 4.5-W-36 4.5 Watts Warm 36° Flood | |
| | | | 4.5-W-60 4.5 Watts Warm 60° Wide Flood | |
| | | 5.5-W-15 5.5 Watts Warm 15° Narrow Spot | | |
| | | 5.5-W-25 5.5 Watts Warm 25° Spot | | |
| | | 5.5-W-36 5.5 Watts Warm 36° Flood | | |
| | | 5.5-W-60 5.5 Watts Warm 60° Wide Flood | | |
| | | NL No Lamp | | |



PROFESSIONAL
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

CONSTRUCTION:

Heavy-gauge, extruded, copper or stainless steel fitted with machined solid brass base.

FINISH:

Brushed Natural Copper or Stainless Steel.
(Brushed copper will rapidly age to an elegant rich bronze-like color and may develop areas of patina over time.)

LENS:

Clear, tempered glass lens.
Optical effect lenses are available

MOUNTING:

Solid brass loop with a six-foot stainless steel cable-hanger included.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 60" pigtail of 18-2 SPT1 UV resistant cable and watertight connectors.

CERTIFICATIONS | STANDARDS | COMPLIANCE:

- UL Certified for wet locations (USA & Canada) | (UL 1838)
- Buy American Act (BAA)
- Build America, Buy America Act (BABA)

LED:

MR-16 LED Lamp.
295 or 389 Lumens.
4.5 or 5.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

DIMENSIONS

