



MODEL 2150-P | Specification Sheet

Commercial Series • Low Voltage • Up / Accent / Downlight

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	4.5 W or 5.5 W
Voltage	9 – 15 VAC
Lumens	295 or 389 Lumens
Lamp Type	MR-16 LED
Housing	Copper or Stainless Steel
Dimensions	2 1/8" DIA x 6 5/8" H

ORDERING INFORMATION

EXAMPLE: HT-2150-CSN-4.5-W-36

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
HT	2150			

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
HT Hanging Downlight	2150	CSN-P Perforated Natural Copper	4.5-W-15 4.5 Watts Warm 15° Narrow Spot	BL Flat Cool Blue Lens
		CSO-P Perforated Olde Copper	4.5-W-25 4.5 Watts Warm 25° Spot	SL Flat Spread Lens
		SS-P Perforated Stainless Steel	4.5-W-36 4.5 Watts Warm 36° Flood	DBL Flat Dark Blue Lens
			4.5-W-60 4.5 Watts Warm 60° Wide Flood	GL Flat Dark Green Lens
			5.5-W-15 5.5 Watts Warm 15° Narrow Spot	RL Flat Red Lens
			5.5-W-25 5.5 Watts Warm 25° Spot	YL Flat Amber Lens
			5.5-W-36 5.5 Watts Warm 36° Flood	HL Honeycomb louver
			5.5-W-60 5.5 Watts Warm 60° Wide Flood	
			NL No Lamp	
		Also available in 18 standard powder coat finishes. See specifications on pg. 2 for description and order codes.		



PROFESSIONAL
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)
Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

CONSTRUCTION:

Heavy-gauge, extruded, copper or stainless steel fitted with machined solid brass base.

FINISH:

Brushed Natural Copper or Stainless Steel.
(Brushed copper will rapidly age to an elegant rich bronze-like color and may develop areas of patina over time.)

Also available in powder coat finish with the following standard colors:

Black (B), Architectural Bronze (Z), Dark Bronze (DZ), Granite (GT), White (W), Architectural Brick (BR), Light Bronze (LZ), Special Bronze (SB), Glossy Gray (GG), Rust (R), Hunter Green (HG), Weathered Bronze (WB), Weathered Iron (WI), Graphite Metallic (GM), Verde (G), Pewter (P), Mocha (M) and Olde Finish (OF).

LENS:

Clear, tempered glass lens.
Optical effect lenses are available

LED:

MR-16 LED Lamp.
295 or 389 Lumens.
4.5 or 5.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

MOUNTING:

Solid brass loop with a six-foot stainless steel cable-hanger included.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 60" pigtail of 18-2 SPT1 UV resistant cable and watertight connectors.

CERTIFICATIONS | STANDARDS | COMPLIANCE:

- UL Certified for wet locations (USA & Canada) | (UL 1838)
- Buy American Act (BAA)
- Build America, Buy America Act (BABA)

DIMENSIONS

