



**MODEL 5273** | Specification Sheet  
Commercial Series • Low Voltage • In-Grade

TYPE:  MODEL:   
PROJECT:

**PRODUCT FEATURES**



Wattage	4.5 W or 5.5 W
Voltage	9 – 15 VAC
Lumens	295 or 389 Lumens
Lamp Type	MR-16 LED
Housing	Injection-Molded Polymer
Dimensions	5" DIA x 6¼" D



**ORDERING INFORMATION**

EXAMPLE: **GW-5273-B-4.5-W-36**

CATEGORY	MODEL	FINISH	LED
	5273		

CATEGORY	MODEL	FINISH	LED	ORDERING NOTES
<b>GW</b> In-Grade	<b>5273</b>	<b>B</b> Black	<b>4.5-W-15</b> 4.5 Watts   Warm   15° Narrow Spot	
<b>CM</b> In-Grade Conduit Mount		<b>Z</b> Architectural Bronze	<b>4.5-W-25</b> 4.5 Watts   Warm   25° Spot	
		<b>DZ</b> Dark Bronze	<b>4.5-W-36</b> 4.5 Watts   Warm   36° Flood	
		<b>GT</b> Granite	<b>4.5-W-60</b> 4.5 Watts   Warm   60° Wide Flood	
		<b>W</b> White	<b>5.5-W-15</b> 5.5 Watts   Warm   15° Narrow Spot	
		<b>BR</b> Architectural Brick	<b>5.5-W-25</b> 5.5 Watts   Warm   25° Spot	
		<b>LZ</b> Light Bronze	<b>5.5-W-36</b> 5.5 Watts   Warm   36° Flood	
		<b>SB</b> Special Bronze	<b>5.5-W-60</b> 5.5 Watts   Warm   60° Wide Flood	
		<b>GG</b> Glossy Gray	<b>NL</b> No Lamp	
		<b>R</b> Rust		
		<b>HG</b> Hunter Green		
		<b>WB</b> Weathered Bronze		
		<b>WI</b> Weathered Iron		
		<b>GM</b> Graphite Metallic		
		<b>G</b> Verde		
		<b>P</b> Pewter		
	<b>M</b> Mocha			
	<b>OF</b> Olde Finish			



PROFESSIONAL  
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



## SPECIFICATIONS

### HOUSING CONSTRUCTION:

Injection-molded glass-reinforced polymer.

### LENS COVER CONSTRUCTION:

Injection-molded glass-reinforced polymer.

### FINISH:

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

### LENS:

Clear, tempered glass lens.  
Optical effect lenses are available.

### MOUNTING:

In-grade. Mounting accessories not required.  
Conduit mount fixtures have two 3/4" NPT inlets on bottom.  
Optional concrete mounting kit available.

### FASTENERS:

All fasteners are stainless steel.

### WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

### CERTIFICATIONS | STANDARDS | COMPLIANCE:

- UL Certified for wet locations (USA & Canada) | (UL 1838)
- Buy American Act (BAA)
- Build America, Buy America Act (BABA)

### LED:

MR-16 LED Lamp.  
295 or 389 Lumens.  
4.5 or 5.5 Watts.

### ELECTRICAL:

Input voltage range 9 - 15 VAC.  
Low voltage transformer required to operate (sold separately).

## DIMENSIONS

