



# MODEL 1215 | Specification Sheet

Commercial Series • Path & Area

TYPE:  MODEL:

PROJECT:

## PRODUCT FEATURES

Wattage	60 W maximum
Voltage	120 VAC
Lamp Type	Candelabra base compatible (lamp not included)
Dimensions	8 1/4" DIA x 24 5/8" H



## ORDERING INFORMATION

EXAMPLE: 1215-B-CR

MODEL	FINISH	LENS
1215		

MODEL	FINISH	LENS
1215	<b>B</b> Black	<b>CR</b> Clear Lens
	<b>Z</b> Architectural Bronze	
	<b>DZ</b> Dark Bronze	
	<b>GT</b> Granite	
	<b>W</b> White	
	<b>BR</b> Architectural Brick	
	<b>LZ</b> Light Bronze	
	<b>SB</b> Special Bronze	
	<b>GG</b> Glossy Gray	
	<b>R</b> Rust	
	<b>HG</b> Hunter Green	
	<b>WB</b> Weathered Bronze	
	<b>WI</b> Weathered Iron	
	<b>GM</b> Graphite Metallic	
	<b>G</b> Verde	
	<b>P</b> Pewter	
	<b>M</b> Mocha	
	<b>OF</b> Olde Finish	



PROFESSIONAL  
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)  
Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction  
of the fixture shown without further notification.



## SPECIFICATIONS

### HOUSING CONSTRUCTION:

Die-cast A360 aluminum.

### STEM CONSTRUCTION:

¼" schedule-40 aluminum pipe.

### FINISH:

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

### LAMP TYPE:

Candelabra base compatible. Lamp not included.

### LENS:

Clear, high-impact polycarbonate lens.

### MOUNTING:

Bottom of stem threaded with ½" NPT.

### FASTENERS:

All fasteners are stainless steel.

### WIRING:

Prewired with 150° C-rated wire.

### CERTIFICATION:

UL Listed to U.S. & Canadian (cUL) safety standards (UL 1598).

## DIMENSIONS

