

	MODEL:		
PROJECT:			

PRODUCT FEATURES







Wattage	2.5 – 5 W
Voltage	9 – 15 VAC
Housing	Injection-Molded Polymer
Dimensions	4¾" DIA × 3" H



ORDERING INFORMATION

EXAMPLE: UW-4217-B-W-LB5ND-DBL

CATEGORY MODEL FINISH LED ACCESSORIES
UW 4217 B

CATEGORY	MODEL	FINISH	LED		ACCESSORIES
UW Underwater	4217	B Black	W-LB2ND	2.5 Watts Warm Integrated LED	DBL Dark Blue Lens
			N-LB2ND	2.5 Watts Neutral Integrated LED	GL Dark Green Lens
			C-LB2ND	2.5 Watts Cool Integrated LED	RL Red Lens
			W-LB5ND	5 Watts Warm Integrated LED	YL Amber Lens
			N-LB5ND	5 Watts Neutral Integrated LED	
			C-LB5ND	5 Watts Cool Integrated LED	
			150-W-G4	1.5 Watts Warm G4 LED Lamp	
			NL	No Lamp	
					ORDERING NOTES
					4217 NOT for use in swimming pools or spas.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Injection-molded polymer.

LENS CONSTRUCTION:

Injection-molded polycarbonate.

LENS:

Clear prismatic spread lens. Optical effect lenses are available.

REFLECTOR

Removable mirror-finish reflector to block up light and provide wider horizontal spread.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Pre-wired with a fifteen-foot pigtail of 18-3 submersible cable. Connectors for a required above-water connection are also included.

CAUTION

Follow installation instructions as well as local electrical codes when installing. **NOT** for use in swimming pools or spas.

CERTIFICATIONS | STANDARDS | COMPLIANCE:

- Buy American Act (BAA)
- Build America, Buy America Act (BABA)

LED:

- Integrated LED Module. 2.5 5 Watts.
- G4 LED Lamp. 1.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC. Low voltage transformer required to operate (sold separately).

DIMENSIONS





