TYPE:	MODEL:
PROJECT:	

# **PRODUCT FEATURES**

c(UL)u





Wattage	4.5 W or 5.5 W
Voltage	9 – 15 VAC
Lumens	295 or 389 Lumens
Lamp Туре	MR-16 LED
Housing	Copper or Stainless Steel
Dimensions	2 1⁄8″ DIA x 6 5⁄8″ H

# **ORDERING INFORMATION**

EXAMPLE: **HT-2150-CSN-4.5-W-36** 

CATEGORY MODEL FINISH LED ACCESSORIES
HT 2150

CATEGORY MODEL		FINISH		LED		ACCESSORIES		
НТ	Hanging Downlight	2150	CSN-P	Perforated Natural Copper	4.5-W-15	4.5 Watts   Warm   15° Narrow Spot	BL	Flat Cool Blue Lens
			SS-P	Perforated Stainless Steel	4.5-W-25	4.5 Watts   Warm   25° Spot	SL	Flat Spread Lens
					4.5-W-36	4.5 Watts   Warm   36° Flood	DBL	Flat Dark Blue Lens
					4.5-W-60	4.5 Watts   Warm   60° Wide Flood	GL	Flat Dark Green Lens
					5.5-W-15	5.5 Watts   Warm   15° Narrow Spot	RL	Flat Red Lens
					5.5-W-25	5.5 Watts   Warm   25° Spot	YL	Flat Amber Lens
					5.5-W-36	5.5 Watts   Warm   36° Flood	HL	Honeycomb louver
					5.5-W-60	5.5 Watts   Warm   60° Wide Flood		
					NL	No Lamp		



# **SPECIFICATIONS**

# **CONSTRUCTION:**

Heavy-gauge, extruded, copper or stainless steel fitted with machined solid brass base.

#### FINISH:

Brushed Natural Copper or Stainless Steel.

(Brushed copper will rapidly age to an elegant rich bronze-like color and may develop areas of patina over time.)

#### LENS

Clear, tempered glass lens. Optical effect lenses are available

### MOUNTING:

Solid brass loop with a six-foot stainless steel cable-hanger included.

### LED:

MR-16 LED Lamp. 295 or 389 Lumens. 4.5 or 5.5 Watts.

### **ELECTRICAL:**

Input voltage range 9 - 15 VAC. Low voltage transformer required to operate (sold separately).

# **FASTENERS:**

All fasteners are stainless steel.

#### WIRING

Prewired with a 36" pigtail of 18-2 SPT1 UV resistant cable and watertight connectors

# **CERTIFICATIONS** | **STANDARDS** | **COMPLIANCE**:

- UL Certified for wet locations (USA & Canada) | (UL 1838)
- Buy American Act (BAA)
- Build America, Buy America Act (BABA)

# **DIMENSIONS**





