



TYPE: MODEL:

PROJECT:

PRODUCT FEATURES

Wattage	300 – 1200 W
Secondary Voltage	12 VAC
Housing	Stainless Steel
Dimensions	17" H x 9" W x 5 1/2" D



ORDERING INFORMATION

EXAMPLE: CTS-600DT

SERIES **MODEL** **OPTIONAL FINISH**

CTS

SERIES	MODEL	OPTIONAL FINISH	ORDERING NOTES
CTS 12 Volt Transformer	300 300 Watts	Clear powder coat finish standard	<p>* See the following for accessory descriptions:</p> <p>T Removable multi-setting mechanical 24-hour timer</p> <p>DT Removable multi-setting digital 7-day timer</p> <p>DA Removable multi-setting digital astronomical timer</p> <p>RP Remote wired photocell with electronic timer</p> <p>Accessories not required for operation of transformer</p>
	300T 300 Watts T timer *	B Black	
	300DT 300 Watts DT timer *	Z Architectural Bronze	
	300DA 300 Watts DA timer *	DZ Dark Bronze	
	300RP 300 Watts RP photocell *	GT Granite	
	600 600 Watts (300 W x 2)	W White	
	600T 600 Watts (300 W x 2) T timer *	BR Architectural Brick	
	600DT 600 Watts (300 W x 2) DT timer *	LZ Light Bronze	
	600DA 600 Watts (300 W x 2) DA timer *	SB Special Bronze	
	600RP 600 Watts (300 W x 2) RP photocell *	GG Glossy Gray	
	900 900 Watts (300 W x 3)	R Rust	
	900T 900 Watts (300 W x 3) T timer *	HG Hunter Green	
	900DT 900 Watts (300 W x 3) DT timer *	WB Weathered Bronze	
	900RP 900 Watts (300 W x 3) RP photocell *	WI Weathered Iron	
	1200 1200 Watts (300 W x 4)	GM Graphite Metallic	
	1200T 1200 Watts (300 W x 4) T timer *	G Verde	
1200DT 1200 Watts (300 W x 4) DT timer *	P Pewter		
1200RP 1200 Watts (300 W x 4) RP photocell *	M Mocha		
	OF Olde Finish		





SPECIFICATIONS

HOUSING CONSTRUCTION:

20-gauge 304 stainless steel.
1/2"– 3/4" knockouts on each side of enclosure for conduit and accessory mounting as well as a removable, swing-down enclosure bottom with Adjustable Cable Raceway Feeder and multiple 1/2"– 3/4" and 2" knockouts.

NEMA ENCLOSURE RATING:

3R

FINISH:

Clear powder coat finish standard. Also available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

TERMINALS:

- Low voltage terminal strip for multiple cable connections
- 120-volt terminal strip for easy hard-wiring and an accessory terminal strip.

PRIMARY PROTECTION:

Auto thermal shut-off

SECONDARY PROTECTION:

Resettable high performance magnetic circuit breaker.
Fully grounded and isolated with encapsulated core and coil.

WIRING:

6-foot, heavy-gauge, grounded, water-resistant power cord with integrally molded plug.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

AVAILABLE POWER RATING:

300, 600, 900 or 1200 Watts

PRIMARY VOLTAGE:

120 Volts
(Also available in 208V, 230V or 277V, 50 or 60 cycle - Special order only.)

SECONDARY VOLTAGE:

12 Volts (with High/Low setting)

DIMENSIONS

