



MODEL 2117 | Specification Sheet

Commercial Series • Low Voltage • Underwater

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES

Wattage	4.5 W or 5.5 W
Voltage	9 – 15 VAC
Lumens	295 or 389 Delivered Lumens
Lamp Type	MR-16 LED
Housing	Injection-Molded Polymer
Dimensions	5" DIA x 5" D

ORDERING INFORMATION

EXAMPLE: UW-2117-B-4.5-W-36-CFR

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
UW	2117			

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
UW Underwater	2117	BSN Natural Brass	4.5-W-15 4.5 Watts Warm 15° Narrow Spot	CFR Crowned Frosted Lens
		BSO Olde Brass	4.5-W-25 4.5 Watts Warm 25° Spot	CBL Crowned Cool Blue Lens
			4.5-W-36 4.5 Watts Warm 36° Flood	SL Flat Spread Lens
			4.5-W-60 4.5 Watts Warm 60° Wide Flood	DBL Flat Dark Blue Lens
			5.5-W-15 5.5 Watts Warm 15° Narrow Spot	GL Flat Dark Green Lens
			5.5-W-25 5.5 Watts Warm 25° Spot	RL Flat Red Lens
			5.5-W-36 5.5 Watts Warm 36° Flood	YL Flat Amber Lens
			5.5-W-60 5.5 Watts Warm 60° Wide Flood	HL Honeycomb louver
			NL No Lamp	
	Also available in 18 standard powder coat finishes. See specifications on pg. 2 for description and order codes.			
				ORDERING NOTES
				Fixtures shipped with specified mounting hardware.



PROFESSIONAL
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)
Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Injection-molded glass-reinforced polymer.

LENS COVER CONSTRUCTION:

Machined Brass.

FINISH:

Natural Brass or Olde Brass lens cover.
Housing available in black only.

Lens Cover also available in powder coat finish with the following standard colors:
Black (B), Architectural Bronze (Z), Dark Bronze (DZ), Granite (GT), White (W),
Architectural Brick (BR), Light Bronze (LZ), Special Bronze (SB), Glossy Gray (GG),
Rust (R), Hunter Green (HG), Weathered Bronze (WB), Weathered Iron (WI),
Graphite Metallic (GM), Verde (G), Pewter (P), Mocha (M) and Olde Finish (OF).

LENS:

Clear, tempered glass lens.
Optical effect lenses are available.

OPTICS/AIMING:

Adjustable mounting bracket provides precise light aiming.
Adjustable lamp bracket provides up to $\pm 25^\circ$ of tilt. Lamp bracket can be locked
into place to prevent disrupting lamp position when relamping.

MOUNTING:

Adjustable mounting bracket mounted on a cement counter weight base for stable
placement underwater.

FASTENERS/INSERTS:

All fasteners are stainless steel with brass inserts.

WIRING:

Pre-wired with a fifteen-foot pigtail of 18-3 submersible cable.
Connectors for a required above-water connection are also included.

CAUTION:

Follow installation instructions as well as local electrical codes when installing.
NOT for use in swimming pools or spas.

LED:

MR-16 LED Lamp.
295 or 389 Lumens.
4.5 or 5.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

LIGHT DISTRIBUTION:

Very Narrow Spot **15** (15°)
Narrow Spot **25** (25°)
Medium Flood **36** (36°)
Wide Flood **60** (60°)

DIMENSIONS

