

| TYPE: | MODEL: |
|----------|--------|
| | |
| PROJECT: | |
| | |

PRODUCT FEATURES

| Wattage | 9 W Max. |
|------------|-------------------|
| Voltage | 9 – 15 VAC |
| Lumens | 295 or 389 Lumens |
| Lamp Type | MR-16 LED |
| Housing | Aluminum |
| Dimensions | 2 ⅓" DIA x 16" H |











ORDERING INFORMATION

LED **MOUNTING** MODEL **FINISH**

BR 2500

| MOUNTING | MODEL | FINISH | | LED | | ORDERING NOTES |
|--------------------------|-------|----------------------|---------------------|-----------------------------|------------------------------------|---------------------------------|
| BR ABS Ground Stake 2500 | 2500 | В | Black | 4.5-W-15 | 4.5 Watts Warm 15° Narrow Spot | Fixtures shipped with specified |
| | z | Architectural Bronze | 4.5-W-25 | 4.5 Watts Warm 25° Spot | mounting hardware. | |
| | | DZ | Dark Bronze | 4.5-W-36 | 4.5 Watts Warm 36° Flood | |
| | | GT | Granite | 4.5-W-60 | 4.5 Watts Warm 60° Wide Flood | |
| | | w | White | 5.5-W-15 | 5.5 Watts Warm 15° Narrow Spot | |
| | | BR | Architectural Brick | 5.5-W-25 | 5.5 Watts Warm 25° Spot | |
| | | LZ | Light Bronze | 5.5-W-36 | 5.5 Watts Warm 36° Flood | |
| | | SB | Special Bronze | 5.5-W-60 | 5.5 Watts Warm 60° Wide Flood | |
| | | GG | Glossy Gray | NL | No Lamp | |
| | | R | Rust | | | |
| | | HG | Hunter Green | | | |
| | | WB | Weathered Bronze | | | |
| | | WI | Weathered Iron | | | |
| | | GM | Graphite Metallic | | | |
| | | G | Verde | | | |
| | | Р | Pewter | | | |
| | | М | Mocha | | | |
| | | OF | Olde Finish | | | |
| | | | | | | |



SPECIFICATIONS

HOUSING CONSTRUCTION:

Die-cast A360 aluminum.

POST CONSTRUCTION:

Heavy-gauge extruded aluminum (1/8" wall thickness).

FINISH

Powder coat finish for Aluminum Door Cover available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

I FNS

Clear, machined acrylic lens.

MOUNTING:

Aluminum mounting base with ABS ground stake included.

LED:

MR-16 LED Lamp. 295 or 389 Lumens. 4.5 or 5.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC. Low voltage transformer required to operate (sold separately).

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATIONS | STANDARDS | COMPLIANCE:

- UL Certified for wet locations (USA & Canada) | (UL 1838)
- Buy American Act (BAA)
- Build America, Buy America Act (BABA)

DIMENSIONS





