

TYPE:	MODEL:
PROJECT:	

вава

BAA

.

PRODUCT FEATURES

Wattage	2.5 – 5 W
Voltage	9 – 15 VAC
Housing	Injection-Molded Polymer
Dimensions	4¾" DIA x 3" H



ORDERING INFORMATION

EXAMPLE: UW-4217-B-W-LB5ND-DBL

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
UW	4217	В		
CATEGORY	MODEL	FINISH	LED	ACCESSORIES
UW Underwater 4217	B Black	W-LB2ND 2.5 Watts Warm Integrated N-LB2ND 2.5 Watts Neutral Integrated C-LB2ND 2.5 Watts Cool Integrated W-LB5ND 5 Watts Warm Integrated N-LB5ND 5 Watts Neutral Integrated N-LB5ND 5 Watts Neutral Integrated C-LB5ND 5 Watts Cool Integrated	ILED GL Dark Green Lens ILED RL Red Lens ILED YL Amber Lens	
			ORDERING NOTES 4217 NOT for use in swimming pools or spas.	



PROFESSIONAL OUTDOOR LIGHTING



SPECIFICATIONS

HOUSING CONSTRUCTION:

Injection-molded polymer.

Injection-molded polycarbonate.

LENS:

Clear prismatic spread lens. Optical effect lenses are available.

REFLECTOR:

Removable mirror-finish reflector to block up light and provide wider horizontal spread.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Pre-wired with a fifteen-foot pigtail of 18-3 submersible cable. Connectors for a required above-water connection are also included.

CAUTION:

Follow installation instructions as well as local electrical codes when installing. **NOT** for use in swimming pools or spas.

CERTIFICATIONS | STANDARDS | COMPLIANCE:

- Buy American Act (BAA)
- Build America, Buy America Act (BABA)


LED:


Integrated LED Module. 2.5 – 5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC. Low voltage transformer required to operate (sold separately).

DIMENSIONS







PROFESSIONAL

OUTDOOR LIGHTING

1625 Surveyor Avenue · Simi Valley, CA 93063 · (805) 527-0987 · (800) 766-VISTA (8478)