TYPE:	MODEL:
PROJECT:	

PRODUCT FEATURES







Wattage	4.5 W or 5.5 W
Voltage	9 – 15 VAC
Lumens	295 or 389 Lumens
Lamp Туре	MR-16 LED
Housing	Copper or Stainless Steel
Dimensions	2 1/8" DIA x 4 1/2" H

ORDERING INFORMATION

EXAMPLE: **HT-2150-CSN-4.5-W-36**

CATEGORY MODEL FINISH LED ACCESSORIES
HT 2150

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
HT Hanging Downlight	2150	CSN Natural Copper	4.5-W-15 4.5 Watts Warm 15° Narrow Spot	BL Flat Cool Blue Lens
		SS Stainless Steel	4.5-W-25 4.5 Watts Warm 25° Spot	SL Flat Spread Lens
			4.5-W-36 4.5 Watts Warm 36° Flood	DBL Flat Dark Blue Lens
			4.5-W-60 4.5 Watts Warm 60° Wide Flood	GL Flat Dark Green Lens
			5.5-W-15 5.5 Watts Warm 15° Narrow Spot	RL Flat Red Lens
			5.5-W-25 5.5 Watts Warm 25° Spot	YL Flat Amber Lens
			5.5-W-36 5.5 Watts Warm 36° Flood	HL Honeycomb louver
			5.5-W-60 5.5 Watts Warm 60° Wide Flood	
			NL No Lamp	



SPECIFICATIONS

CONSTRUCTION:

Heavy-gauge, extruded, copper or stainless steel fitted with machined solid brass base.

FINISH:

Brushed Natural Copper or Stainless Steel.

(Brushed copper will rapidly age to an elegant rich bronze-like color and may develop areas of patina over time.)

LENS

Clear, tempered glass lens. Optical effect lenses are available

MOUNTING:

Solid brass loop with a six-foot stainless steel cable-hanger included.

LED:

MR-16 LED Lamp. 295 or 389 Lumens. 4.5 or 5.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.

Low voltage transformer required to operate (sold separately).

FASTENERS:

All fasteners are stainless steel.

WIRING

Prewired with a 60" pigtail of 18-2 SPT1 UV resistant cable and watertight

CERTIFICATIONS | **STANDARDS** | **COMPLIANCE**:

- UL Certified for wet locations (USA & Canada) | (UL 1838)
- Buy American Act (BAA)
- Build America, Buy America Act (BABA)

DIMENSIONS





