

TYPE:	MODEL:
PROJECT:	

PRODUCT FEATURES

c(UL)u





Wattage	1 W
Voltage	9 – 15 VAC
ССТ	3000K (WARM) 5000K (COOL)
Faceplate	Aluminum, Brass, Copper or Stainless Steel
Dimensions	5¾"L x 1"H x 3¼"D

ORDERING INFORMATION

EXAMPLE: **SL-4260-BSN-W-LB2ND**

CATEGORY MODEL FINISH LED

SL 4260

CATEGORY	MODEL	FINISH			LED		
SL Step Light	4260	В	Black	R	Rust	W-LB2ND	1 Watt Warm Integrated LED
		z	Architectural Bronze	HG	Hunter Green	C-LB2ND	1 Watt Cool Integrated LED
		DZ	Dark Bronze	WB	Weathered Bronze		
		GT	Granite	WI	Weathered Iron		
		w	White	GM	Graphite Metallic		
		BR	Architectural Brick	G	Verde		
		LZ	Light Bronze	P	Pewter		
		SB	Special Bronze	М	Mocha		
		GG	Glossy Gray	OF	Olde Finish		
		BSN	Natural Brass	CSN	Natural Copper		
		BSO	Olde Brass	SS	Stainless Steel		



SPECIFICATIONS

FACEPLATE CONSTRUCTION:

Aluminum, Brass, Copper or Stainless Steel.

HOUSING CONSTRUCTION:

Die-cast A360 aluminum.

FLANGE CONSTRUCTION:

Aluminum, Brass, Copper or Stainless Steel.

FINISH:

Aluminum Housing available with Powder coat finish in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

LENS:

Textured, high-impact polycarbonate lens.

LED:

Integrated LED Module.

1 Watt.

COLOR TEMPERATURE:

3000K or 5000K CCT White.

ELECTRICAL:

Input voltage range 9 - 15 VAC. Low voltage transformer required to operate (sold separately).

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a ten-foot pigtail of 18-2 SPT1 cable and underground connectors.

CERTIFICATIONS | STANDARDS | COMPLIANCE:

- UL Certified for wet locations (USA & Canada) | (UL 1838)
- Buy American Act (BAA)
- Build America, Buy America Act (BABA)

DIMENSIONS



