

## **PRODUCT FEATURES**

Wattage	1 – 5 W
Voltage	9 – 15 VAC
Housing	Aluminum
Dimensions	4″ DIA x 15 %″ H





# **ORDERING INFORMATION**

EXAMPLE: **PR-2265-B-150-W-G4** 

 MOUNTING
 MODEL
 FINISH
 LED

 PR
 2265
 150-W-G4

MOUNTING	MODEL	FINISH	LED	ORDERING NOTES
PR ABS Ground Stake	2265	B Black Z Architectural Bronze	<b>150-W-G4</b> 1.5 Watts   Warm   G4 LED Lamp	Fixtures shipped with specified mounting hardware.
		DZ Dark Bronze GT Granite		Custom length stems available - Consult local distributor.
		<b>W</b> White		
		BR Architectural Brick  LZ Light Bronze		
		SB Special Bronze		
		GG Glossy Gray  R Rust		
		HG Hunter Green		
		WB Weathered Bronze WI Weathered Iron		
		GM Graphite Metallic		
		G Verde		
		P Pewter  M Mocha		
		<b>OF</b> Olde Finish		



## **SPECIFICATIONS**

## **HOUSING CONSTRUCTION:**

Die-cast A360 aluminum.

### **STEM CONSTRUCTION:**

½" schedule-40 aluminum pipe.

#### FINISH

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

#### I FNS

Clear, high-impact polycarbonate lens.

### MOUNTING:

Bottom of stem threaded with ½" NPT.

# LED:

G4 LED Lamp. 1.5 Watts.

## **ELECTRICAL:**

Input voltage range 9 - 15 VAC. Low voltage transformer required to operate (sold separately).

## **FASTENERS:**

All fasteners are stainless steel.

### WIRING

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

#### CERTIFICATION

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

# **DIMENSIONS**





