



MODEL 2142 | Specification Sheet
Commercial Series • Low Voltage • Step Light

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage 5 W Max.

Voltage 9 – 15 VAC

Faceplate Brass, Copper or Stainless Steel

Dimensions 4 ¾" L x 2 7/8" H x 3 ½" D

ORDERING INFORMATION

EXAMPLE: **SL-2142-BSN-W-LB5ND**

CATEGORY SL **MODEL** 2142 **FINISH** **LED**

CATEGORY	MODEL	FINISH	LED
SL Step Light	2142	BSN Natural Brass	W-LB2ND 2 Watts Warm Integrated LED
		BSO Olde Brass	N-LB2ND 2 Watts Neutral Integrated LED
		CSN Natural Copper	C-LB2ND 2 Watts Cool Integrated LED
		SS Stainless Steel	W-LB5ND 4 Watts Warm Integrated LED
			N-LB5ND 4 Watts Neutral Integrated LED
			C-LB5ND 4 Watts Cool Integrated LED
		NL No Lamp	



PROFESSIONAL
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Stamped & formed aluminum recessed box with 1/2" knockouts on the back & side.

COVER PLATE CONSTRUCTION:

Stamped solid brass, copper, or stainless steel.

LENS:

Translucent, high-impact polycarbonate lens.

MOUNTING:

Recessed mounting box included.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATIONS | STANDARDS | COMPLIANCE:

- UL Certified for wet locations (USA & Canada) | (UL 1838)
- Buy American Act (BAA)
- Build America, Buy America Act (BABA)

LED:

- Integrated LED Module. 2 – 4 Watts.
- G4 LED Lamp. 1.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

DIMENSIONS

